| Catalog Number | |
|---|---|
| Notes | |
| Type | |

Contractor Select™

# CMR Series

## Ceiling Mount Sensor



The CMR is a line voltage sensor that easily mounts directly to a ceiling. Lens options include large motion extended range and small motion standard range. These sensors are capable of covering an entire private office or small room by themselves. A line voltage sensor provides one relay for a single-level control. For rooms with obstructions, these sensors are also offered with Dual Technology, which adds Microphonics™ detection to the Passive Infrared (PIR) detection.

### FEATURES:

- PIR Occupancy Detection
- 360° Coverage
- Self-Contained Relay - No Power Pack needed
- Time Delay: 30 sec to 20 min
- No Minimum Load Requirements
- Push-Button Programmable
- Green LED Indicator
- 100 Hr. Lamp Burn-in Timer Mode

| Catalog Number | UPC | Decription | Detection Type | Coverage | Voltage Type | Color | Voltage | Pallet Quantity |
|---|---|---|---|---|---|---|---|---|
| CMR 9 | 745975808281 | Ceiling Mount Sensor | Passive Infrared (PIR) | Small Motion 360° | Line | White | 120/277/220/230 | 96 |
| CMR PDT 9 | 745975809448 | Ceiling Mount Sensor | Passive Dual Technology (PDT) | Small Motion 360° | Line | White | 120/277/220/230 | 96 |
| CMR 10 | 745975808250 | Ceiling Mount Sensor | Passive Infrared (PIR) | Large Motion 360° | Line | White | 120/277/220/230 | 96 |

More configurations are available. Click here or visit www.acuitybrands.com and search for CMR Series.

## Specifications

**INSTALLATION:**

Suitable for mounting directly to a ceiling tile or a metallic grid (two self-tapping screws provided). Sensor's mounting holes also align with 3.5" octagon or single gang handy box (screws not provided). Sensor will detect motions crossing segments more effectively than motions parallel to beams.

**LISTINGS:**

CSA certified to US and Canadian safety standards.


For use in ambient operating temperatures ranging from -10°C to 60°C.

**WARRANTY:**

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:
www.acuitybrands.com/support/warranty/terms-and-conditions

**Note**: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.

## Dimensions




All dimensions are inches (centimeters) unless otherwise indicated.


© 2018-2022 Acuity Brands Lighting, Inc. All rights reserved. Rev. 06/09/22

| Catalog Number | |
|---|---|
| Notes | |
| Type | |

Contractor Select™

# CMR Series

## Ceiling Mount Sensor



The CMR is a line voltage sensor that easily mounts directly to a ceiling. Lens options include large motion extended range and small motion standard range. These sensors are capable of covering an entire private office or small room by themselves. A line voltage sensor provides one relay for a single-level control. For rooms with obstructions, these sensors are also offered with Dual Technology, which adds Microphonics™ detection to the Passive Infrared (PIR) detection.

### FEATURES:

- PIR Occupancy Detection
- 360° Coverage
- Self-Contained Relay - No Power Pack needed
- Time Delay: 30 sec to 20 min
- No Minimum Load Requirements
- Push-Button Programmable
- Green LED Indicator
- 100 Hr. Lamp Burn-in Timer Mode

| Catalog Number | UPC | Decription | Detection Type | Coverage | Voltage Type | Color | Voltage | Pallet Quantity |
|---|---|---|---|---|---|---|---|---|
| CMR 9 | 745975808281 | Ceiling Mount Sensor | Passive Infrared (PIR) | Small Motion 360° | Line | White | 120/277/220/230 | 96 |
| CMR PDT 9 | 745975809448 | Ceiling Mount Sensor | Passive Dual Technology (PDT) | Small Motion 360° | Line | White | 120/277/220/230 | 96 |
| CMR 10 | 745975808250 | Ceiling Mount Sensor | Passive Infrared (PIR) | Large Motion 360° | Line | White | 120/277/220/230 | 96 |

More configurations are available. Click here or visit www.acuitybrands.com and search for CMR Series.

## Specifications

**INSTALLATION:**

Suitable for mounting directly to a ceiling tile or a metallic grid (two self-tapping screws provided). Sensor's mounting holes also align with 3.5" octagon or single gang handy box (screws not provided). Sensor will detect motions crossing segments more effectively than motions parallel to beams.

**LISTINGS:**

CSA certified to US and Canadian safety standards.


For use in ambient operating temperatures ranging from -10°C to 60°C.

**WARRANTY:**

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:
www.acuitybrands.com/support/warranty/terms-and-conditions

**Note**: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.

## Dimensions




All dimensions are inches (centimeters) unless otherwise indicated.


© 2018-2022 Acuity Brands Lighting, Inc. All rights reserved. Rev. 06/09/22