



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## CPL212 2-1/2" PVC Coupling

*Cantex, Inc*

Catalog Number	CPL212
Manufacturer	Cantex, Inc
Description	Cantex 6141629 Is A 2-1/2 In. Schedule 40 Standard Center Stop Coupling Used to Join Lengths Of Conduit Pipe Together With Two Solvent Weld Socket Ends
Weight per unit	0.3500 (lbs/each)
Product Category	PVC Conduit Fittings & Accy

### Features

Inside Diameter	2.875
outside diameter	3.250
Schedule	40

### Material, Color, and Finish

Color	Gray
-------	------

### Dimensions and Weight

Length	3.5
Size	2-1/2 in. Schedule 40 Standard Center Stop Coupling

### Descriptions

Description	2-1/2" PVC COUPLING
extra long description	CTX 6141629 2 1/2 UL CPLG CC
Features	CANTEX 6141629 is a 2-1/2 in. Schedule 40 Standard Center Stop Coupling used to join lengths of conduit pipe together with two solvent weld socket ends
Long Description	CANTEX 6141629 is a 2-1/2 in. Schedule 40 Standard Center Stop Coupling used to join lengths of conduit pipe together with two solvent weld socket ends
Product Type	2 1/2 UI CPLG CC
Special Features	Center stop to help determine proper depth of connection

### Manufacturer Information

Brand	PVC & Accessories
GTIN	00088700567344
Manufacturers Part Number	6141629
UPC	088700061071

### Taxonomies, Classifications, and Categories

Category Description	COUPLINGS, ADAPTERS, REDUCERS, BUSHINGS, & CAPS
Type	2-1/2 in. Schedule 40 Standard Center Stop Coupling;Schedule 40 Standard Center Stop Coupling



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

**Trade Size**

Trade Size ..... 2 1/2 .....

**Packaging**

Carton ..... 1 .....

Package ..... 20 .....

Weight Per each ..... 0.35 .....

**Uses, Certifications, and Standards**

Application ..... Schedule 40 Standard Center Stop Coupling .....

standard ..... UL Listed .....