

Service Entrance Splices

Standard 2" length compression splices.

Aluminum Service Entrance Compression Splices — U 1 B™ and CS™ 5/8" Die Series

- Constructed from aluminum for high conductivity
- Solid center barriers and large chamfers for easy cable insertion
- Prefilled with oxide inhibitor to prevent oxidation and keep out moisture
- All splices are color coded and marked with strip lengths, installation die codes and compression locations, providing easy identification for easy installation
- Comply with ANSI C119.4 when properly installed on aluminum-to-aluminum or aluminum-to-copper conductors
- RUS Accepted



U 1 B 1010 EC



CS73

U 1 B SERIES CAT. NO.	CS SERIES CAT. NO.	CONDUCTOR A				CONDUCTOR B			
		COLOR	ACSR	STR.	SOL.	COLOR	ACSR	STR.	SOL.
U 1 B 11	—	BROWN	—	#10	#8	BROWN	—	#10	#8
U 1 B 88	CS61	GREEN	—	#8	#6	GREEN	—	#8	#6
U 1 B 81	—	BLUE	#6 (6/1)	—	#4	BROWN	—	#10	#8
U 1 B 66	CS64					BLUE	#6 (6/1)	—	#4
U 1 B 68	CS63			GREEN	—	#8	#6		
U 1 B 61	CS62			BROWN	—	#10	#8		
U 1 B 612	—	ORANGE	#4 (6/1, 7/1)	6	#2	BLACK	—	#12	#10
U 1 B 44	CS68			ORANGE		#4 (6/1, 7/1)	—	#2	
U 1 B 46	CS67			BLUE		#6 (6/1)	—	#4	
U 1 B 48	CS66			GREEN		—	#8	#6	
U 1 B 41	CS65	BROWN	—	#10	#8				
U 1 B 22	CS73	RED	#2 (6/1, 7/1)	#1 & #2	#1	RED	#2 (6/1, 7/1)	#1 & #2	#1
U 1 B 24	CS72					ORANGE	#4 (6/1, 7/1)	—	#2
U 1 B 26	CS71					BLUE	#6 (6/1)	—	#4
U 1 B 28	CS70					GREEN	—	#8	#6
U 1 B 21	CS69	BROWN	—	#10	#8				
U 1 B 1010	CS78	YELLOW	1/0 (6/1)	1/0	#1	YELLOW	1/0 (6/1)	1/0	—
U 1 B 102	CS77					RED	#2 (6/1, 7/1)	#1 & #2	#1
U 1 B 104	CS76					ORANGE	#4 (6/1, 7/1)	—	#2
U 1 B 106	CS75					BLUE	#6 (6/1)	—	#4
U 1 B 108	CS74	GREEN	—	#8	#6				
—	CS84	GRAY	—	2/0	—	YELLOW	1/0 (6/1)	1/0	—
—	CS85					GRAY	—	2/0	—

Service Entrance Splices

Standard 2" length compression splices.

Aluminum Service Entrance Compression Splices — U 1 B™ and CS™ 5/8" Die Series

- Constructed from aluminum for high conductivity
- Solid center barriers and large chamfers for easy cable insertion
- Prefilled with oxide inhibitor to prevent oxidation and keep out moisture
- All splices are color coded and marked with strip lengths, installation die codes and compression locations, providing easy identification for easy installation
- Comply with ANSI C119.4 when properly installed on aluminum-to-aluminum or aluminum-to-copper conductors
- RUS Accepted



U 1 B 1010 EC



CS73

U 1 B SERIES CAT. NO.	CS SERIES CAT. NO.	CONDUCTOR A				CONDUCTOR B			
		COLOR	ACSR	STR.	SOL.	COLOR	ACSR	STR.	SOL.
U 1 B 11	—	BROWN	—	#10	#8	BROWN	—	#10	#8
U 1 B 88	CS61	GREEN	—	#8	#6	GREEN	—	#8	#6
U 1 B 81	—	BLUE	#6 (6/1)	—	#4	BROWN	—	#10	#8
U 1 B 66	CS64					BLUE	#6 (6/1)	—	#4
U 1 B 68	CS63					GREEN	—	#8	#6
U 1 B 61	CS62					BROWN	—	#10	#8
U 1 B 612	—	ORANGE	#4 (6/1, 7/1)	—	#2	BLACK	—	#12	#10
U 1 B 44	CS68					ORANGE	#4 (6/1, 7/1)	—	#2
U 1 B 46	CS67					BLUE	#6 (6/1)	—	#4
U 1 B 48	CS66					GREEN	—	#8	#6
U 1 B 41	CS65	BROWN	—	#10	#8				
U 1 B 22	CS73	RED	#2 (6/1, 7/1)	#1 & #2	#1	RED	#2 (6/1, 7/1)	#1 & #2	#1
U 1 B 24	CS72					ORANGE	#4 (6/1, 7/1)	—	#2
U 1 B 26	CS71					BLUE	#6 (6/1)	—	#4
U 1 B 28	CS70					GREEN	—	#8	#6
U 1 B 21	CS69	BROWN	—	#10	#8				
U 1 B 1010	CS78	YELLOW	1/0 (6/1)	1/0	#1	YELLOW	1/0 (6/1)	1/0	—
U 1 B 102	CS77					RED	#2 (6/1, 7/1)	#1 & #2	#1
U 1 B 104	CS76					ORANGE	#4 (6/1, 7/1)	—	#2
U 1 B 106	CS75					BLUE	#6 (6/1)	—	#4
U 1 B 108	CS74	GREEN	—	#8	#6				
—	CS84	GRAY	—	2/0	—	YELLOW	1/0 (6/1)	1/0	—
—	CS85					GRAY	—	2/0	—