



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2450 NE Inner Loop Building 1  
78626-0000, TX Georgetown  
Phone: 737-444-2615  
Fax: 737-444-2617



## CS73 1 to 1 Alcu Comp Splice

*Abb Installation Products, Inc*

Catalog Number	CS73
Manufacturer	Abb Installation Products, Inc
Description	Service Entrance Compression Splice, #2 Awg (Ascr );#1 and #2 Awg (Stranded );#1 Awg (Solid ) Conductor Size, Non-Insulated, Copper/Aluminum Conductor Material, 2 In Overall Length, Compression/Crimp Terminal, 0.05 LB/Ea
Weight per unit	0.0500 (lbs/each)
Product Category	Large Terminals & Connectors

### Features

connection	Compression
insulation	None
Material	Aluminum
Number of Conductors	2

### Dimensions and Weight

Size	2 INCH
------	--------

### Descriptions

Description	1 TO 1 ALCU COMP SPLICE
extra long description	ABB CS73 AL SERVENTR COMP SPLICE A:

### Manufacturer Information

Brand	Blackburn Mechanical
GTIN	00783786100613
UPC	783786100613

### Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Type	Compression Splice Service Entrance

### Packaging

Carton	100
Package	500
Weight Per each	0.05



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2450 NE Inner Loop Building 1  
78626-0000, TX Georgetown  
Phone: 737-444-2615  
Fax: 737-444-2617

## Uses, Certifications, and Standards

Application

Basic, uninsulated Splices for Service Entrances. For  
Combinations of Aluminum-to-Aluminum or  
Aluminum-to-Copper Conductors

environmental conditions

All Seasons / Conditions

Mounting

None

standard

RUS Accepted. Complies with ANSI C119.4 when properly  
installed on Aluminum-to-Aluminum or Aluminum-to-Copper  
Conductors / RUS Accepted. Complies with ANSI C119.4 when  
properly installed on Aluminum-to-Aluminum or  
Aluminum-to-Copper Conductors