

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **CT106 3-4 Main Copper C Tap** *Nsi Industries*

EBBAN	
Catalog Number	CT106
Manufacturer	Nsi Industries
Description	Copper C Tap Grounding Connector For 3 to 4 Awg Copper "C" Taps Ensure Positive, All Around Compression With Low-Resistance and High Pull-Out Values. Made Of High Conductivity Copper, They Satisfy The Requirements Of NEC250-81 and 250-91 For Connecting to The Grounding
Maight governit	Electrode System. Rated 600 Volts.
Weight per unit	
Product Category	Large Terminals & Connectors
Features	
Conductor Size	
Material	Copper
Tap Size	
Voltage Rating	
Warranty	1 YEAR
Material, Color, and Finish	
Color	Pink
Finish	COPPER
Dimensions and Weight	
Size	4-4 AWG
Descriptions	
Description	3-4 MAIN COPPER C TAP
extra long description	NSI CT-106 Copper C Tap 3-4 Main
Features	Copper C Tap Grounding Connector for 3 to 4 AWG Copper "C" Taps ensure positive, all around compression with low-resistance and high pull-out values. Made of high conductivity copper, they satisfy the requirements of NEC250-81 and 250-91 for connecting to the grounding electrode system. Rated 600 Volts.
Long Description	Copper C Tap Grounding Connector for 3 to 4 AWG Copper "C" Taps ensure positive, all around compression with low-resistance and high pull-out values. Made of high conductivity copper, they satisfy the requirements of NEC250-81 and 250-91 for connecting to the grounding electrode system. Rated 600 Volts.
Product Type	Copper C Tap 3-4 Main
Special Features	4-4 AWG



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

N	lanuf	actur	er In	forma	tion
---	-------	-------	-------	-------	------

Brand	NSi
GTIN	00662381098054
Manufacturers Part Number	CT-106
UPC	662381098054

#### **Taxonomies, Classifications, and Categories**

Category Description	Comp & Mech Lugs and Butt Splices
Type	C-Taps

#### Packaging

,,,ag.,,g		
Carton	1	
Package		
Weight Per each	0.04	

### Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors	
environmental conditions	90 C	
standard	UL486	
Temperature Rating	90 C	