

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CVS2100XMM CVS 2P 100AS 42KA 240 Vac Load Terms W/Hardware *Eaton Corp*

Catalog Number	CVS2100XMM
Manufacturer	Eaton Corp
Description	Eaton Type CV Molded Case Circuit Breaker, Molded Case Circuit Breaker, 100 A, 42 Kaic, Two-Pole, #6 - 4/0 Al/Cu, CV, #4/0 Kcmil Maximum Load, Includes Mounting Kit
Weight per unit	4.0 (lbs/each)
Product Category	2 Pole
Features	
Current Rating	100 A
dimensions	7.5000 IN X 3.5000 IN X 5.0000 IN
interrupt rating	42 kAIC
Poles	2
Descriptions	
Description	CVS 2P 100AS 42KA 240 VAC LOAD TERMS W/HARDWARE
extra long description	ETN CVS2100XMM CVS 2 POLE 100 AMPS
Features	Eaton's main circuit breakers are used in a variety of applications including the main or emergency disconnect on the outside of a house, a tenant main breaker in group metering stacks and feed-through lug blocks specifically designed for sub-feeding from an existing panel. Main breakers are available with a variety of accessories including shunt trip, bell alarms and auxiliary switches.
Long Description	Eaton Type CV Molded Case Circuit Breaker, Molded case circuit breaker, 100 A, 42 kAIC, Two-pole, #6 - 4/0 AI/Cu, CV, #4/0 kcmil maximum load, Includes mounting kit
Product Type	CVS 2 Pole 100 Amps 42KA 240 Vac
Manufacturer Information	
Brand	EATON CUTLER-HAMMER
GTIN	00786685705880
Manufacturers Part Number	CVS2100XMM
UPC	786685705880
Taxonomies, Classifications, and C	Categories
Category Description	MOUDED CACE DEFAUEDS
Туре	Tenant main breaker
Doole a minor	
Packaging	
Packaging Carton	1

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

oco, oci tiricationo, ana otan	uai us
Application	Datacenters - IT Space: CI and Hyper ConvergedGeneration -
	Renewable Energy - Alternative EnergyGeneration - Conventional
	Energy - Conventional EnergyOtherMarine Vessels and
	Equipment - Marine Vessels and Equipment - Other
standard	UL 489,CSA Std. C22.2 No. 5