

# Specifications



## Eaton D3PR5A

D3 Series General Purpose Plug-In Relay, Latching cover, 11 pins, 120V coil, 10,000 Ohms resistance, Octal terminal, DPDT contact configuration, 16A contact rating, Silver alloy contacts, IP40 enclosure

### General specifications

<b>PRODUCT NAME</b>	Eaton General-purpose relay
<b>CATALOG NUMBER</b>	D3PR5A
<b>UPC</b>	782114227732
<b>PRODUCT LENGTH/DEPTH</b>	2 in
<b>PRODUCT HEIGHT</b>	2 in
<b>PRODUCT WIDTH</b>	1 in
<b>PRODUCT WEIGHT</b>	0.5 lb
<b>COMPLIANCES</b>	CE Marked RoHS Compliant
<b>CERTIFICATIONS</b>	CSA Certified UL Listed cRUus

## Product specifications

TYPE	General-purpose relay
COVER	Latching
OPTIONS	Plain cover relay
COIL VOLTAGE	120 V
CONTACT CONFIGURATION	DPDT
CONTACT MATERIAL	Silver alloy
CONTACT RATING	16 A
ENCLOSURE	IP40
NUMBER OF PINS	11
RESISTANCE	10,000 $\Omega$
SERIES	D3
TERMINALS	Octal
VOLTAGE - MAX	300 V switching

## Resources

### SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - D3PR5A](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.



# Specifications



## Eaton D3PR5A

D3 Series General Purpose Plug-In Relay, Latching cover, 11 pins, 120V coil, 10,000 Ohms resistance, Octal terminal, DPDT contact configuration, 16A contact rating, Silver alloy contacts, IP40 enclosure

### General specifications

<b>PRODUCT NAME</b>	Eaton General-purpose relay
<b>CATALOG NUMBER</b>	D3PR5A
<b>UPC</b>	782114227732
<b>PRODUCT LENGTH/DEPTH</b>	2 in
<b>PRODUCT HEIGHT</b>	2 in
<b>PRODUCT WIDTH</b>	1 in
<b>PRODUCT WEIGHT</b>	0.5 lb
<b>COMPLIANCES</b>	CE Marked RoHS Compliant
<b>CERTIFICATIONS</b>	CSA Certified UL Listed cRUus



Powering Business Worldwide

## Product specifications

TYPE	General-purpose relay
COVER	Latching
OPTIONS	Plain cover relay
COIL VOLTAGE	120 V
CONTACT CONFIGURATION	DPDT
CONTACT MATERIAL	Silver alloy
CONTACT RATING	16 A
ENCLOSURE	IP40
NUMBER OF PINS	11
RESISTANCE	10,000 $\Omega$
SERIES	D3
TERMINALS	Octal
VOLTAGE - MAX	300 V switching

## Resources

### SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - D3PR5A](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

