

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



DS222 20A 150V 2W3P Iron RCPT U Shape/RND Cont *Crouse-Hinds*

Catalog Number	DS222
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series DS Receptacle Housing, Feraloy Iron Alloy, Two-Wire, Three-Pole, 20A, 125 Vac, For Plugs With U Shaped or Round Grounding Contacts
Weight per unit	1.2 (lbs/each)
Product Category	FS & FD Type Boxes & Covers
atures	
amperage rating	20
dimensions	4.2500 IN X 1.5000 IN X 2.7500 IN
Poles	3
Voltage Rating	125 VAC
scriptions	
Description	20A 150V 2W3P IRON RCPT U SHAPE/RND CONT
extra long description	CRS-H DS222 20A 150V 2W3P IRON RCPT
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hul configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series DS receptacle housing, Feraloy iron alloy, Two-wire, three-pole, 20A, 125 Vac, For plugs with U shaped or round grounding contacts
Product Type	20A 150V 2W3P Iron RCPT U Shape/RND Cont
Special Features	With Cover, Weatherproof
nufacturer Information	
Brand	Crouse-Hinds
GTIN	00782274230207
Manufacturers Part Number	DS222
UPC	782274230207

Taxonomies, Classifications, and Categories

Type Receptacle housing



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Availability Status	Inactive
Packaging Carton	1
Weight Per each	1.18
Uses, Certifications, and Standards Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 498, UL 514A, CSA C22.2