

ELLIOTE ELECTRIC SUPPLY Mo Deliver Lower Cost. Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



E30.750BK6"P Thin-Wall Heat Shrink Tubing, BK, 3/4-6" *Minnesota Mining (3M)*

| Catalog Number | E30.750BK6"P |
|---------------------------|--|
| Manufacturer | Minnesota Mining (3M) |
| Description | 3M [™] Heat Shrink Tubing Eps-300 Is A Dual Wall Tubing Provides The Advantage Of An Integral, Adhesive Lined Construction. This Flame Retardant Tubing With A 3:1 Shrink Ratio Offers Insulation For 600V Rated Applications. The Flexible Polyolefin Construction Features An Internal Layer Of Thermoplastic Adhesive, Which Offers Moisture Seal Protection In Automotive and Marine Applications. |
| Weight per unit | 0.0305 (lbs/each) |
| Product Category | Splicing & Terminating Kits |
| scriptions | |
| Description | THIN-WALL HEAT SHRINK TUBING, BK, 3/4-6" |
| extra long description | 3M 7000133685 3M™ Thin-Wall Heat Sh |
| Features | 3M [™] Heat Shrink Tubing EPS-300 is color coded for quick and easy identification of the wire. It provides a skintight fit and strain relief protection for electronic components, wire splices, wire bundles and harness breakouts. This flame retardant tubing has a heat shrinkable outer wall that is irradiation cross linked for abrasion resistance and helps to maintain the high flow as well as good adhesion characteristics. When the tubing cools down, it forms a permanent, water resistant barrier. It withstands |
| Long Description | 3M [™] Heat Shrink Tubing EPS-300 is a dual wall tubing provides the advantage of an integral, adhesive lined construction. This flame retardant tubing with a 3:1 shrink ratio offers insulation for 600V rated applications. The flexible polyolefin construction features an internal layer of thermoplastic adhesive, which offers moisture seal protection in automotive and marine applications. |
| Product Type | 3M [™] Thin-Wall Heat Shrink Tubing Eps-300 |
| Special Features | Adhesive Lined Flexible Pilyolefin |
| nufacturer Information | |
| Brand | 3M |
| GTIN | 00051128600689 |
| Manufacturers Part Number | E30.750BK6"P |
| | |

Taxonomies, Classifications, and Categories

UPC

| inditionities, diassifications, and | categories |
|-------------------------------------|----------------------------|
| Category Description | HEAT/COLD SHRINK |
| Туре | Dual Wall (Adhesive Lined) |

051128600689



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

| Carton | 1 | |
|-----------------|--------|--|
| Package | 10 | |
| Weight Per each | 0.0305 | |

Uses, Certifications, and Standards

| standard | |
|----------|--|
|----------|--|

UL, ABS, CSA