

# U-Line® Factory Sealed 15 and 20 Amp Plugs

## Explosionproof, Dust-Ignitionproof

These watertight plugs also fit NEMA 5-15R, 5-20R or 6-20R receptacles in nonclassified areas. Choice of Aluminum or Thermoplastic Polyester Plug.

Class I, Division 1 and 2 Groups B, C, D  
 Class II, Division 1 and 2 Group G and Coal Dust  
 Class III  
 CSA Type 7BCD, 9G

### Applications

- U-Line® Interchanger™ ECP plug: suitable for use in such areas as refineries, petrochemical plants, and other areas subject to where ignitable gases are present.
- NCP Plug: ideal where moisture or corrosion is a constant problem, such as production facilities on marine platforms, and pipeline transportation facilities.











### Features

- Unique blade-type, brass contacts exert constant pressure along entire contact surface and provide superior electrical contact.
- Insulators provide superior dielectric and mechanical strength and lowest arc tracking.
- Longer plug housing for better gripping and easier plug insertion and withdrawal.


- Plugs fits any standard non-explosionproof receptacle (NEMA 5-15R, 5-20R, or 6-20R) as well as U-Line explosionproof receptacles.
- 15 Amp ECP1523 125 Vac and 20 Amp ECP2023 125 Vac U-Line plugs are for use in the T-slot configured 20 Amp U-Line receptacle. ie ECSK-2023.
- ECP plug: a twist of the plug produces audible “click” to indicate fast make and break of built-in switch contacts. Twisting plug locks it in place and cannot be accidentally pulled out.
- NCP plug: special neoprene watertight plug bushing accommodates flexible cord ranging from .538” to .639” diameter.

### Standard Materials

- ECP plug: copperfree (less than 4/10ths of 1%) aluminum
- NCP plug: 30% glass-reinforced thermoplastic polyester

	Amp	Diagram	Wire/ Pole	Cable Dia., (Inches)	Catalog Number	
					125 Vac 	250 Vac 
<b>U-Line® Interchanger™ ECP Standard Plug</b>						
	15		2W, 3P	.538 to .639	<b>ECP-1523</b>	—
	20		2W, 3P	.538 to .639	<b>ECP-2023</b>	—
	20		2W, 3P	.538 to .639	—	<b>ECP-20232</b>
<b>NCP Plug</b>						
	15		2W, 3P	.538 to .639	<b>NCP-1523</b>	—
	20		2W, 3P	.538 to .639	<b>NCP-2023</b>	—
	20		2W, 3P	.538 to .639	—	<b>NCP-20232</b>

### Dimensions



 CSA Certification only.

# U-Line® Factory Sealed 15 and 20 Amp Plugs

## Explosionproof, Dust-Ignitionproof

These watertight plugs also fit NEMA 5-15R, 5-20R or 6-20R receptacles in nonclassified areas. Choice of Aluminum or Thermoplastic Polyester Plug.

Class I, Division 1 and 2 Groups B, C, D  
 Class II, Division 1 and 2 Group G and Coal Dust  
 Class III  
 CSA Type 7BCD, 9G

### Applications

- U-Line® Interchanger™ ECP plug: suitable for use in such areas as refineries, petrochemical plants, and other areas subject to where ignitable gases are present.
- NCP Plug: ideal where moisture or corrosion is a constant problem, such as production facilities on marine platforms, and pipeline transportation facilities.











### Features

- Unique blade-type, brass contacts exert constant pressure along entire contact surface and provide superior electrical contact.
- Insulators provide superior dielectric and mechanical strength and lowest arc tracking.
- Longer plug housing for better gripping and easier plug insertion and withdrawal.


- Plugs fits any standard non-explosionproof receptacle (NEMA 5-15R, 5-20R, or 6-20R) as well as U-Line explosionproof receptacles.
- 15 Amp ECP1523 125 Vac and 20 Amp ECP2023 125 Vac U-Line plugs are for use in the T-slot configured 20 Amp U-Line receptacle. ie ECSK-2023.
- ECP plug: a twist of the plug produces audible “click” to indicate fast make and break of built-in switch contacts. Twisting plug locks it in place and cannot be accidentally pulled out.
- NCP plug: special neoprene watertight plug bushing accommodates flexible cord ranging from .538” to .639” diameter.

### Standard Materials

- ECP plug: copperfree (less than 4/10ths of 1%) aluminum
- NCP plug: 30% glass-reinforced thermoplastic polyester

	Amp	Diagram	Wire/ Pole	Cable Dia., (Inches)	Catalog Number	
					125 Vac 	250 Vac 
<b>U-Line® Interchanger™ ECP Standard Plug</b>						
	15		2W, 3P	.538 to .639	<b>ECP-1523</b>	—
	20		2W, 3P	.538 to .639	<b>ECP-2023</b>	—
	20		2W, 3P	.538 to .639	—	<b>ECP-20232</b>
<b>NCP Plug</b>						
	15		2W, 3P	.538 to .639	<b>NCP-1523</b>	—
	20		2W, 3P	.538 to .639	<b>NCP-2023</b>	—
	20		2W, 3P	.538 to .639	—	<b>NCP-20232</b>

### Dimensions



 CSA Certification only.