

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Lithonia Lighting - Acu	
Catalog Number Manufacturer	Lithonia Lighting - Acuity
Description	The Lithonia Lighting Basics Ecrg, Is A Combination Of Exit and
Description	Emergency Lighting. The Ecrg Is Ideal For Safely Illumination of Exit and Path Of Egress Above-The-Door In Small Spaces At Lower Mounting Heights While Providing 90 Minutes Of Emergency Power. Contains Ability to Switch Between Red and Green Letters. Features Test Switch and Status Indicator.
Weight per unit	4.0 (lbs/each)
Product Category	Lighting
atures	
average life	100,000
dimensions	19.09 x 4.33 x 7.95
Fixture Type	Emergency Exit Sign
Hardware	No
Lamp Included	Yes
Lamp Туре	LED - Static
lumens	113
Material	Thermoplastic
Shape	Square
Voltage Rating	120/277 V
aterial, Color, and Finish	
color rendering index (cri)	75
color temperature	6200
Finish	Textured
mensions and Weight	
Height	7.95
Length	19.09
Width	4.33



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions	
Construction	New Construction, Remodel
Description	LED EXIT COMBO RED/GREEN SWITCHABLE SQ HEADS RMT C
extra long description	LITH ECRG HO SQ M6 Thermoplastic LE
Features	Contractor Select
Long Description	The Lithonia Lighting Basics ECRG, is a combination of exit and emergency lighting. The ECRG is ideal for safely illuminating the path of egress above-the-door in small spaces at lower mounting heights while providing 90 minutes of emergency power. Contains ability to switch between red and green letters. Features test switch and status indicator.
Product Type	Emergency Exit Sign
Manufacturer Information	
Brand	Lithonia Lighting
GTIN	00194994900504
Manufacturers Part Number	ECRG HO SQ M6
UPC	194994900504
Taxonomies, Classifications, and Cate	gories
Category Description	Emergency & Exit Lighting
Туре	Emergency Exit Sign
Packaging	
Carton	
Weight Per each	3.97
Uses, Certifications, and Standards	
Application	Education,Government,Healthcare,Hospitality,House of Worship,Offices & Banks,Retail
environmental conditions	Indoor
Mounting	SURFACE
standard	NFPA 101,NFPA 70,ULCA Title 20