

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



EV1410FBQ 16-14AWG #10STD Blue Fork TRML Panduit Corporation

Catalog Number	EV1410FBQ	
Manufacturer	Panduit Corporation	
Description	Stronghold EV14-10FB-Q Contractor Grade Insulated Fork Terminals Are A Reliable and Economical Option That Withstand A Wide Range Of General-Purpose Applications. The Fork Design Provides For Fast and Easy Installation, Without The Need to Remove Fastener. Accommodates 16-14 Awg, Compatible With #10 Stud (M5), Are Blue In Color, and Come In Packages Of 25.	
Weight per unit	0.0500 (lbs/each)	
Product Category	Small Terminals & Connectors	
Features		
connection	Funnel	
insulation	Vinyl	
Material	Copper	
media	Yes	
Wire Size	#14	
Material, Color, and Finish		
Color	Blue	
Finish	Tinned	
Dimensions and Weight		
Size	#10	
Descriptions		
Description	16-14AWG #10STD BLUE FORK TRML	
extra long description	PAN EV14-10FB-Q StrongHold™ EV14-10	
Long Description	StrongHold EV14-10FB-Q Contractor Grade Insulated Fork	
	Terminals are a reliable and economical option that withstand a	
	wide range of general-purpose applications. The fork design	
	provides for fast and easy installation, without the need to	
	remove fastener. Accommodates 16-14 AWG, compatible with	
Product Type	#10 Stud (M5), are blue in color, and come in packages of 25. Stronghold™ EV14-10FB-Q Loose Piece Forks, Blue, Vinyl, 1/5"	
5.	Stronghold LVIT TOID-Q LOOSET ICCE TOIRS, DIGE, VIIIYI, 1/3	
Manufacturer Information	Donduit®	
Brand	Panduit®	
GTIN	00613056366435	
Manufacturers Part Number	EV14-10FB-Q	
UPC	613056366435	



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories		
Category Description	TERMINALS	
Туре	Fork Terminal	
Packaging		
Carton	25	
Package	250	
Weight Per each	0.05	
Uses, Certifications, and Standa	ırds	
Mounting	0.31	

UL Listed 587H E52164; CSA Certified LR31212