

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



EV186FBQ 22-18AWG #6STD Red Fork TRML

Panduit Corporation

Catalog Number	EV186FBQ
Manufacturer	Panduit Corporation
Description	Stronghold EV18-6FB-Q Contractor Grade Insulated Fork Terminals Are A Reliable and Economical Option That Withstand A Wide Range Of General-Purpose Applications. The Fork Design Provides For Fast and Easy Installation, Without The Need to Remove Fastener. Accommodates 22-18 Awg, Compatible With #6 Stud (M3.5), Are Red In Color, and Come In Packages Of 25.
Weight per unit	0.0700 (lbs/each)
Product Category	Small Terminals & Connectors
Features	
connection	Funnel
insulation	Vinyl
Material	Copper
media	Yes
Wire Size	#18
Material, Color, and Finish	
Color	Red
Finish	Tinned
Dimensions and Weight	
Size	#6
Descriptions	
Description	22-18AWG #6STD RED FORK TRML
extra long description	PAN EV18-6FB-Q StrongHold™ EV18-6FB
Long Description	StrongHold EV18-6FB-Q Contractor Grade Insulated Fork
	Terminals are a reliable and economical option that withstand a
	wide range of general-purpose applications. The fork design
	provides for fast and easy installation, without the need to
	remove fastener. Accommodates 22-18 AWG, compatible with
Draduat Tupo	#6 Stud (M3.5), are red in color, and come in packages of 25.
Product Type	Stronghold™ EV18-6FB-Q Loose Piece Forks, Red, Vinyl, 1/8" S
Manufacturer Information	D I. 110
Brand	Panduit®
GTIN Manufacturers Part Number	00613056366442
Manufacturers Part Number UPC	EV18-6FB-Q
UPC	613056366442



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories		
Category Description	TERMINALS	
Туре	Fork Terminal	
Packaging		
Carton	25	
Package	250	
Weight Per each	0.07	
Uses, Certifications, and Standard	ds	
Mounting	0.31	

UL Listed 587H E52164; CSA Certified LR31212