

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Carton

Weight Per each

EYS56SA 1-1/2" Alu Cond Seal

Crouse-Hinds	
Catalog Number	EYS56SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eys Conduit Sealing Fitting, Male and Female, Copper-Free Aluminum, Vertical or Horizontal, 1-1/2"
Weight per unit	1.4 (lbs/each)
Product Category	Aluminum
eatures	
connection	Male Threaded, Female Threaded
dimensions	2.4400 IN X 2.4400 IN X 5.5000 IN
Descriptions	
Description	1-1/2" ALU COND SEAL
extra long description	CRS-H EYS56 SA 1 1/2 NPT MALE/FEM A
Features Long Description	Crouse-Hinds series EYS and EZS explosionproof sealing fittings restrict the passage of gases, vapors or flames from one portion of the electrical installation to another, limit explosions to the sealed off enclosure, and limit pre-compression or "pressure piling" in conduit systems. EYS sealing fittings are available for installation in either vertical only or in both horizontal or vertica positions. They are available in a variety of materials, including Feraloy iron alloy and/or ductile iron, copper-Eaton Crouse-Hinds series EYS conduit sealing fitting, Male and
	female, Copper-free aluminum, Vertical or horizontal, 1-1/2"
Product Type	1 1/2 NPT Male/Fem Al Vert/Horz Seal FTG
Special Features	Horizontal/Vertical Position
Vlanufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274379418
Manufacturers Part Number	EYS56 SA
UPC	782274379418
Taxonomies, Classifications, and (Categories
Category Description	HAZARDOUS LOCATION FITTINGS
Туре	Conduit sealing fitting
Packaging	
Conton	2

2

1.38

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	CLASS I DIV 1 2 GROUP C D, CLASS II DIV 1 2 GROUP E F G, CLASS
	III
standard	UL 886, CSA C22.2