

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



F1.5X4WH6 1-1/2X4X72" NM WHT NRW SLT Wire Duct Panduit Corporation

Catalog Number	F1.5X4WH6
Manufacturer	Panduit Corporation
Description	The F1.5X4WH6 Panduct Lead-Free PVC Narrow Slot Wiring Duct
	Features A Narrow Slot/Finger Design That Closely Matches The
	Spacing Of High-Density Components. Upper and Lower Scorelines Allow For Easy Finger/Sidewall Section Removal. UI 94
	Flame Class Of V-0 With A UI Recognized Continuous-Use
	Temperature Up to 122°F (50°C). Mounting Holes Provided.
	Lead-Free PVC. 1.5" X 4" (38.1 MM X 101.6 MM) and 6' (1.83 M)
	Long. Cover Sold Separately. Color White.
Weight per unit	0.4400 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray
Features	
connection	Mounting Holes
media	Yes
Material, Color, and Finish	
Color	White
Dimensions and Weight	
Height	4.10
Length	6.00
Size	1.50 x 4.00
Width	1.75
Descriptions	
Description	1-1/2X4X72" NM WHT NRW SLT WIRE DUCT
extra long description	PAN F1.5X4WH6 Panduct [®] F1.5X4WH6 Ba
Long Description	The F1.5X4WH6 Panduct Lead-Free PVC Narrow Slot Wiring Duct
	features a narrow slot/finger design that closely matches the
	spacing of high-density components. Upper and lower scorelines
	allow for easy finger/sidewall section removal. UL 94 flame class
	of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. Lead-free PVC. 1.5" x 4"
	(38.1 mm x 101.6 mm) and 6' (1.83 m) long. Cover sold
	separately. Color White.
Product Type	Panduct® F1.5X4WH6 Base Wiring Duct
	J



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	PANDUIT
GTIN	00074983375400
Manufacturers Part Number	F1.5X4WH6
UPC	074983375400
Taxonomies, Classifications, and Cate	gories
Category Description	WIRE DUCT AND COVERS
Туре	Base Wiring Duct
Availability	
minimum qty	
Packaging	
Carton	6
Package	60
Weight Per foot	0.44
Uses, Certifications, and Standards	
Application	Narrow slot/finger design provides more slots to fit the spacing of high-density terminal block applications
standard	CSA Approved;RoHS Compliant, UL Recognized, CE Compliant