

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



F3X3WH6 3X3X72" WHT SLTD Wire Duct Panduit Corporation

Catalog Number	F3X3WH6
Manufacturer	Panduit Corporation
Description	The F3X3WH6 Panduct Lead-Free PVC Narrow Slot Wiring Duct Features A Narrow Slot/Finger Design That Closely Matches The Spacing Of High-Density Components. Upper and Lower Scorelines Allow For Easy Finger/Sidewall Section Removal. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). Mounting Holes Provided. Lead-Free PVC. 3" X 3" (76.2 MM X 76.2 MM) and 6' (1.83 M) Long. Cover Sold Separately. Color White.
Weight per unit	
Product Category	
Features	
connection	Mounting Holes
Material	PVC
media	Yes
Material, Color, and Finish	
Color	White
Dimensions and Weight	
Height	3.12
Length	NA
Size	3.00 x 3.00
Width	3.25
Descriptions	
Description	3X3X72" WHT SLTD WIRE DUCT
extra long description	PAN F3X3WH6 Panduct® F3X3WH6 Base W
Long Description	The F3X3WH6 Panduct Lead-Free PVC Narrow Slot Wiring Duct features a narrow slot/finger design that closely matches the spacing of high-density components. Upper and lower scorelines allow for easy finger/sidewall section removal. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. Lead-free PVC. 3" x 3" (76.2 mm x 76.2 mm) and 6' (1.83 m) long. Cover sold separately. Color White.
Product Type	Panduct® F3X3WH6 Base Wiring Duct



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer	Information
Drand	

Brand	PANDUIT
GTIN	00074983375769
Manufacturers Part Number	F3X3WH6
UPC	074983375769

Taxonomies, Classifications, and Categories

Category Description	WIRE DUCT AND COVERS	
Туре	Base Wiring Duct	
ailability		

Availability

minimum qty c	minimum qty		6
---------------	-------------	--	---

Packaging

ckaging		
Carton	6	
Package	60	
Weight Per foot	0.46	

Uses, Certifications, and Standards

Application	Narrow slot/finger design provides more slots to fit the spacing
	of high-density terminal block applications
standard	CSA Approved:RoHS Compliant, UL Recognized, CE Compliant