

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



**Product Type** 

### **F4X4LG6 4" X 4" Narrow Slot LT Gray Duct** *Panduit Corporation*

| Catalog Number               | F4X4LG6   |  |
|------------------------------|---|--|
| Manufacturer                 | Panduit Corporation   |  |
| Description                  | The F4X4LG6 Panduct Lead-Free PVC Narrow Slot Wiring Duct         |  |
|                              | Features A Narrow Slot/Finger Design That Closely Matches The     |  |
|                              | Spacing Of High-Density Components. Upper and Lower               |  |
|                              | Scorelines Allow For Easy Finger/Sidewall Section Removal. UI 94  |  |
|                              | Flame Class Of V-0 With A UI Recognized Continuous-Use            |  |
|                              | Temperature Up to 122°F (50°C). Mounting Holes Provided.          |  |
|                              | Lead-Free PVC. 4" X 4" (101.6 MM X 101.6 MM) and 6' (1.83 M)      |  |
|                              | Long. Cover Sold Separately. Color Light Gray.                    |  |
| Weight per unit              |   |  |
| Product Category             | Ducts, Raceways, Runways, Tray                                    |  |
| Features                     |   |  |
| connection                   | Mounting Holes  |  |
| media                        | Yes   |  |
| Material, Color, and Finish  |   |  |
| Color                        | Gray  |  |
| <b>Dimensions and Weight</b> |   |  |
| Height                       | 4.10  |  |
| Length                       | NA  |  |
| Size                         | 4.00 x 4.00   |  |
| Width                        | 4.25  |  |
| Descriptions                 |   |  |
| Description                  | 4" X 4" NARROW SLOT LT GRAY DUCT                                  |  |
| extra long description       | PAN F4X4LG6 Panduct® F4X4LG6 Base W                               |  |
| Long Description             | The F4X4LG6 Panduct Lead-Free PVC Narrow Slot Wiring Duct         |  |
|                              | features a narrow slot/finger design that closely matches the     |  |
|                              | spacing of high-density components. Upper and lower scorelines    |  |
|                              | allow for easy finger/sidewall section removal. UL 94 flame class |  |
|                              | of V-0 with a UL recognized continuous-use temperature up to      |  |
|                              | 122°F (50°C). Mounting holes provided. Lead-free PVC. 4" x 4"     |  |
|                              | (101.6 mm x 101.6 mm) and 6' (1.83 m) long. Cover sold            |  |
|                              | separately. Color Light Gray.                                     |  |
| 5 · · <del>-</del>           |   |  |

Panduct® F4X4LG6 Base Wiring Duct



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Manutac | turer In | torma | tion |
|---------|----------|-------|------|
|---------|----------|-------|------|

| Brand                     | PANDUIT        |  |
|---------------------------|----------------|--|
| GTIN                      | 00074983375974 |  |
| Manufacturers Part Number | F4X4LG6        |  |
| UPC                       | 074983375974   |  |

#### **Taxonomies, Classifications, and Categories**

| Category Description | WIRE DUCT AND COVERS |
|----------------------|----------------------|
| Туре                 | Base Wiring Duct     |
|                      |                      |

#### **Availability**

minimum qty 6

#### **Packaging**

| ckayırıy        |       |  |
|-----------------|-------|--|
| Carton          | 6     |  |
| Package         | 60    |  |
| Weight Per each | 0.658 |  |

#### Uses, Certifications, and Standards

| Application | Narrow slot/finger design provides more slots to fit the spacing |  |
|-------------|--|--|
|             | of high-density terminal block applications                      |  |
| standard    | CSA Approved:RoHS Compliant, UL Recognized, CE Compliant         |  |