





GE  
Lighting

### 85384 - FLE14/2/TC16SWCD

GE energy smart® CFL 14 watt Postlight 1-pack

- 2700K soft white light appearance
- 60 watt replacement uses only 14 watts
- Estimated yearly energy costs \$1.69 based on 3 hours per day \$0.11 per kWh
- GE energy smart® CFL features a GE Spiral® bulb on the inside that uses 75% less energy and lasts up to 5 times longer than incandescents. Use GE energy smart® CFL bulbs in enclosed outdoor fixtures like porch lights, postlights and carriage lights
- Lasts 9.1 years based on 3 hours per day usage
- Postlight with medium base for use in outdoor carriage and post lights



#### CAUTIONS & WARNINGS

##### Warning

- Risk of Electric Shock
  - Do not open - no user serviceable parts inside.
  - Do not use where directly exposed to water or outdoors without an enclosed fixture.

##### NOTES

- Fluorescent lamp lumens decline during life
- Lumens on one piece self ballasted lamp systems are measured base up.
- Use only on 120V 60 Hz circuits. Do not use on dimming circuits, photocells or timers. Do not use in wet locations.
- Amalgam product experience stable brightness over a wider temperature range and in various operating positions.

#### GENERAL CHARACTERISTICS

|                            |  |
|----------------------------|--|
| Lamp Type                  | Compact Fluorescent - Self-Ballasted               |
| Bulb                       | TC16   |
| Base                       | Medium Screw (E26)                                 |
| Equivalent Wattage         | 60.0 W   |
| Rated Life (Vert)          | 10000.0 h  |
| Rated Life                 | 10000.0 hrs  |
| Starting Temperature (MIN) | 5.0 °C   |
| Life in Years              | 9.1  |
| LEED-EB MR Credit          | 467 picograms Hg per mean lumen hour               |
| Primary Application        | Retail<br>Display;Hospitality;Office;Restaurant;Fa |

#### PHOTOMETRIC CHARACTERISTICS

|                                 |          |
|---------------------------------|----------|
| Initial Lumens (Vert)           | 750.0    |
| Initial Lumens                  | 750.0    |
| Initial Lumens (Hor)            | 53.57143 |
| Mean Lumens                     | 600.0    |
| Nominal Initial Lumens per Watt | 53       |
| Color Temperature               | 2700.0 K |
| Color Rendering Index (CRI)     | 82.0     |

#### ELECTRICAL CHARACTERISTICS

|                                |          |
|--------------------------------|----------|
| Wattage                        | 14.0     |
| Voltage (MIN)                  | 14.0     |
| Voltage                        | 120.0    |
| Input Voltage                  | 120.0 V  |
| Estimated Energy Cost per Year | 1.69     |
| Input Current                  | 0.2200 A |

#### DIMENSIONS

|                              |                     |
|------------------------------|---------------------|
| Maximum Overall Length (MOL) | 5.0000 in(127.0 mm) |
| Nominal Length               | 5.000 in(127.0 mm)  |

#### PRODUCT INFORMATION

|                                  |                  |
|----------------------------------|------------------|
| Product Code                     | 85384            |
| Description                      | FLE14/2/TC16SWCD |
| Standard Package                 | BUNDLE           |
| Standard Package GTIN            | 10043168853849   |
| Standard Package Quantity        | 12               |
| Sales Unit                       | Unit             |
| No Of Items Per Sales Unit       | 1                |
| No Of Items Per Standard Package | 12               |
| UPC                              | 043168853842     |





GE  
Lighting

### 85384 - FLE14/2/TC16SWCD

GE energy smart® CFL 14 watt Postlight 1-pack

- 2700K soft white light appearance
- 60 watt replacement uses only 14 watts
- Estimated yearly energy costs \$1.69 based on 3 hours per day \$0.11 per kWh
- GE energy smart® CFL features a GE Spiral® bulb on the inside that uses 75% less energy and lasts up to 5 times longer than incandescents. Use GE energy smart® CFL bulbs in enclosed outdoor fixtures like porch lights, postlights and carriage lights
- Lasts 9.1 years based on 3 hours per day usage
- Postlight with medium base for use in outdoor carriage and post lights



#### CAUTIONS & WARNINGS

##### Warning

- Risk of Electric Shock
  - Do not open - no user serviceable parts inside.
  - Do not use where directly exposed to water or outdoors without an enclosed fixture.

##### NOTES

- Fluorescent lamp lumens decline during life
- Lumens on one piece self ballasted lamp systems are measured base up.
- Use only on 120V 60 Hz circuits. Do not use on dimming circuits, photocells or timers. Do not use in wet locations.
- Amalgam product experience stable brightness over a wider temperature range and in various operating positions.

#### GENERAL CHARACTERISTICS

|                            |  |
|----------------------------|--|
| Lamp Type                  | Compact Fluorescent - Self-Ballasted               |
| Bulb                       | TC16   |
| Base                       | Medium Screw (E26)                                 |
| Equivalent Wattage         | 60.0 W   |
| Rated Life (Vert)          | 10000.0 h  |
| Rated Life                 | 10000.0 hrs  |
| Starting Temperature (MIN) | 5.0 °C   |
| Life in Years              | 9.1  |
| LEED-EB MR Credit          | 467 picograms Hg per mean lumen hour               |
| Primary Application        | Retail<br>Display;Hospitality;Office;Restaurant;Fa |

#### PHOTOMETRIC CHARACTERISTICS

|                                 |          |
|---------------------------------|----------|
| Initial Lumens (Vert)           | 750.0    |
| Initial Lumens                  | 750.0    |
| Initial Lumens (Hor)            | 53.57143 |
| Mean Lumens                     | 600.0    |
| Nominal Initial Lumens per Watt | 53       |
| Color Temperature               | 2700.0 K |
| Color Rendering Index (CRI)     | 82.0     |

#### ELECTRICAL CHARACTERISTICS

|                                |          |
|--------------------------------|----------|
| Wattage                        | 14.0     |
| Voltage (MIN)                  | 14.0     |
| Voltage                        | 120.0    |
| Input Voltage                  | 120.0 V  |
| Estimated Energy Cost per Year | 1.69     |
| Input Current                  | 0.2200 A |

#### DIMENSIONS

|                              |                     |
|------------------------------|---------------------|
| Maximum Overall Length (MOL) | 5.0000 in(127.0 mm) |
| Nominal Length               | 5.000 in(127.0 mm)  |

#### PRODUCT INFORMATION

|                                  |                  |
|----------------------------------|------------------|
| Product Code                     | 85384            |
| Description                      | FLE14/2/TC16SWCD |
| Standard Package                 | BUNDLE           |
| Standard Package GTIN            | 10043168853849   |
| Standard Package Quantity        | 12               |
| Sales Unit                       | Unit             |
| No Of Items Per Sales Unit       | 1                |
| No Of Items Per Standard Package | 12               |
| UPC                              | 043168853842     |