

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FRNR110 110A 250V TD Class RK5 Dual Elem Fuse-Fusetron Bussmann Fuses

Catalog Number	FRNR110
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK5 Fuse, FRN-R, Time-Delay, Dual-Element, Current Limiting Fuse, 110 A, Non-Indicating Fuse, Interrupting Rating Of 200 Ka At 250 Vac and 20 Ka At 125 VDC
Weight per unit	0.8000 (lbs/each)
Product Category	Dual Element
Features	
amperage rating	110 A
class	Class RK5
connection	
dimensions	2.0000 IN X 0.5600 IN X 0.5600 IN
element	Dual
Fuse Class	Class RK5
interrupt rating	20 kAIC at 125 Vdc200 kAIC at 250 Vac
media	Yes
Response Time	
Voltage Rating	250 VAC, 125 VDC
Dimensions and Weight	
Size	1.56 In Diameter X 7.13 In Length
Descriptions	
Description	110A 250V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRN-R-110 FUSETRON DUAL-ELEMEN
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500 of rated current (8 seconds for 1/10-30A sizes)
Long Description	Eaton Bussmann Series Class RK5 fuse, FRN-R, time-delay, dual-element, current limiting fuse, 110 A, non-indicating fuse, interrupting rating of 200 kA at 250 Vac and 20 kA at 125 Vdc
Product Type	Fusetron Dual-Element



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

и	•	IABLIT	· ^ ^ †	COLID	forma	STIAN
•	•	141111	41 1111	~		4116311

Brand	Eaton Bussmann series
GTIN	00051712507448
Manufacturers Part Number	FRN-R-110
UPC	051712507448

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSF

Packaging

onaging	
Carton	1
Weight Per each	0.8

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked