



## FRNR412 4-1/2A 250V TD Class RK5 Dual Elem Fuse-Fusetron

*Bussmann Fuses*

Catalog Number	FRNR412
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK5 Fuse, FRN-R, Time-Delay, Dual-Element, Current Limiting Fuse, 4.5 A, Non-Indicating Fuse, Interrupting Rating Of 200 Ka At 250 Vac and 20 Ka At 125 VDC
Weight per unit	0.0500 (lbs/each)
Product Category	Dual Element

### Features

amperage rating	4.5
connection	Ferrule End X Ferrule End
dimensions	2.0000 IN X 0.5600 IN X 0.5600 IN
element	Dual
Fuse Class	Class RK5
interrupt rating	20 kAIC at 125 Vdc200 kAIC at 250 Vac
media	Yes
Response Time	10 S at 500%
Voltage Rating	250 VAC, 125 VDC

### Dimensions and Weight

Size	0.56 In Diameter X 2.00 In Length
------	-----------------------------------

### Descriptions

Description	4-1/2A 250V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRN-R-4-1/2 FUSETRON DUAL-ELEM
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500 of rated current (8 seconds for 1/10-30A sizes).
Long Description	Eaton Bussmann Series Class RK5 fuse, FRN-R, time-delay, dual-element, current limiting fuse, 4.5 A, non-indicating fuse, interrupting rating of 200 kA at 250 Vac and 20 kA at 125 Vdc
Product Type	Fusetron Dual-Element Class RK5



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1725 East Highway 82  
76240-0000, TX Gainesville  
Phone: 940-612-1388  
Fax: 940-612-1499

## Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712507219
Manufacturers Part Number	FRN-R-4-1/2
UPC	051712507219

## Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE

## Packaging

Carton	10
Weight Per each	0.05

## Uses, Certifications, and Standards

Application standard	Ind Facilities & Factories - Facility: Safety and Security Systems CE Marked
----------------------	---