

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## FRNR7 7A 250V TD Class RK5 Dual Elem Fuse-Fusetron Bussmann Fuses

| Catalog Number         | FRNR7                                                                                                                                                                                       |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Manufacturer           | Bussmann Fuses                                                                                                                                                                              |
| Description            | Eaton Bussmann Series Class RK5 Fuse, FRN-R, Time-Delay,<br>Dual-Element, Current Limiting Fuse, 7 A, Non-Indicating Fuse,<br>Interrupting Rating Of 200 Ka At 250 Vac and 20 Ka At 125 VDC |
| Weight per unit        | 0.0600 (lbs/each)                                                                                                                                                                           |
| Product Category       | Dual Element                                                                                                                                                                                |
| Features               |                                                                                                                                                                                             |
| amperage rating        | 7 A                                                                                                                                                                                         |
| class                  | Class RK5                                                                                                                                                                                   |
| connection             |                                                                                                                                                                                             |
| dimensions             | 2.0000 IN X 0.5600 IN X 0.5600 IN                                                                                                                                                           |
| element                | Dual                                                                                                                                                                                        |
| Fuse Class             | Class RK5                                                                                                                                                                                   |
| interrupt rating       | 20 kAIC at 125 Vdc200 kAIC at 250 Vac                                                                                                                                                       |
| media                  |                                                                                                                                                                                             |
| Response Time          |                                                                                                                                                                                             |
| Voltage Rating         | 250 VAC, 125 VDC                                                                                                                                                                            |
| Dimensions and Weight  |                                                                                                                                                                                             |
| Size                   | 0.56 In Diameter X 2.00 In Length                                                                                                                                                           |
| Descriptions           |                                                                                                                                                                                             |
| Description            | 7A 250V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON                                                                                                                                                |
| extra long description |                                                                                                                                                                                             |
| Features               | Bussmann's UL Class RK5 Fusetron product offering provides                                                                                                                                  |
|                        | energy efficient advanced protection with its dual-element,                                                                                                                                 |
|                        | time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and                                                                 |
|                        | 600Vac, 200kA RMS Sym interrupting rating and sizes ranging                                                                                                                                 |
|                        | from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of                                                                                                                               |
| Long Decorintian       | time-delay at 500 of rated current (8 seconds for 1/10-30A sizes).                                                                                                                          |
| Long Description       | Eaton Bussmann Series Class RK5 fuse, FRN-R, time-delay,                                                                                                                                    |
|                        | dual-element, current limiting fuse, 7 A, non-indicating fuse,<br>interrupting rating of 200 kA at 250 Vac and 20 kA at 125 Vdc                                                             |
| Product Type           | Fusetron Dual-Element Class RK5                                                                                                                                                             |
| Troduct Type           |                                                                                                                                                                                             |



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Manufacturer Information**

| Brand                                 | Eaton                                                              |
|---------------------------------------|--------------------------------------------------------------------|
| GTIN                                  | 00051712507257                                                     |
| Manufacturers Part Number             | FRN-R-7                                                            |
| UPC                                   | 051712507257                                                       |
| Taxonomies, Classifications, and Cate | egories                                                            |
| Category Description                  | Fuses & Fuse Accessories                                           |
| Туре                                  | FUSE                                                               |
| Packaging                             |                                                                    |
| Carton                                | 10                                                                 |
| Weight Per each                       | 0.06                                                               |
| Uses, Certifications, and Standards   |                                                                    |
| Application                           | Ind Facilities & Factories - Facility: Safety and Security Systems |
| standard                              | Contact factory,CE Marked                                          |