

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FRNR90 90A 250V Dual Elem RK5 TD Fuse Fusetron

Bussmann Fuses

Catalog Number	FRNR90
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK5 Fuse, FRN-R, Time-Delay,
	Dual-Element, Current Limiting Fuse, 90 A, Non-Indicating Fuse,
	Interrupting Rating Of 200 Ka At 250 Vac
Weight per unit	0.3100 (lbs/each)
Product Category	Dual Element
atures	
amperage rating	90 A

Fea

amperage rating	90 A
class	Class RK5
connection	Blade End X Blade End
dimensions	5.8800 IN X 1.0000 IN X 1.0000 IN
element	Dual
Fuse Class	Class RK5
interrupt rating	20 kAIC at 125 Vdc200 kAIC at 250 Vac
media	Yes
Response Time	10 S at 500%
Voltage Rating	250 VAC, 125 VDC

Dimensions and Weight

1.06 In Diameter X 5.88 In Length Size

Descri

scriptions	
Description	90A 250V DUAL ELEM RK5 TD FUSE FUSETRON
extra long description	BUSS FRN-R-90 FUSETRON DUAL-ELEMENT
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500 of rated current (8 seconds for 1/10-30A sizes).
Long Description	Eaton Bussmann Series Class RK5 fuse, FRN-R, time-delay, dual-element, current limiting fuse, 90 A, non-indicating fuse, interrupting rating of 200 kA at 250 Vac
Product Type	Fusetron Dual-Element Class RK5



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

м	١.	_		4	c _	_ 1				c _					
ľ	۱,	12	n	111		CI		·Δr	' In	ГЛ	rr	ทว	1	n	n
	v			u	а	L - I	u	C-1	'In	W		110		w	

Brand	Eaton Bussmann series
GTIN	00051712507424
Manufacturers Part Number	FRNR90
UPC	051712507424

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSF

Packaging

Carton	5
Weight Per each	0.31

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked