

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

Alloy

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FSC2 1G FS-Dev Box, 3/4" Crouse-Hinds

Catalog Number	FSC2
Manufacturer	Crouse-Hinds
Description	Device Box, Single Gang Box Style, Electrogalvanized and Aluminum Acrylic Paint, Shallow, 3/4 In Trade Size, 2 Hubs, 3/4 In Hub Size, End Hub Location, 2.75 In Width, 6.03 In Height, Surface Mount, 2.42 LB/Ea
Weight per unit	2.4 (lbs/each)
Product Category	FS & FD Type Boxes & Covers
Features	
Cable Entry	(1) Each End
dimensions	6.0300 IN X 1.8800 IN X 2.7500 IN

Electrogalvanized With Aluminum Acrylic Painted Feraloy Iron

Dimensions and Weight

Size 3/4 in

Descriptions

Material

Description	1G FS-DEV BOX, 3/4"
extra long description	CRS-H FSC2 3/4 THRUFEED CST IRON BX
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Special Features	Configuration Type FSC, With Mounting Lug and Ground Screw, Dimension 2-3/4 In Width X 1-7/8 In Depth X 6-1/32 In Height

Manufacturer Information

Brand	Eaton
GTIN	00782274410708
LIPC.	782274410708

Taxonomies, Classifications, and Categories

Category Description	FS BOXES AND COVERS
Туре	DEVICE BOX



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	5
Weight Per each	2.42
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	FLUSH

UL 514, CSA C22.2, Federal Specification W-C-5860