

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



G3X2LG6 SLTD Wiring Duct Panduit Corporation

Catalog Number	G3X2LG6
Manufacturer	Panduit Corporation
Description	The G3X2LG6 Panduct Lead-Free PVC Wide Slot Wiring Duct Feature A Wide Slot/Finger Design That Provides Greater
	Sidewall Rigidity and Is Suitable With A Range Of Wire Bundle
	Sizes. UI 94 Flame Class Of V-0 With A UI Recognized
	Continuous-Use Temperature Up to 122°F (50°C). Mounting
	Holes Provided. 3.0" X 2.0" (76.2. MM X 50.8 MM) and 6' (1.8 M)
	Long. Cover Sold Separately. Color Light Gray.
Weight per unit	0.0166 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray
- eatures	
connection	Mounting Holes
Material	PVC
media	Yes
Material, Color, and Finish	
Color	Gray
Dimensions and Weight	
Length	6.00
Size	3.25 x 2.12
Width	3.25
Descriptions	
Description	SLTD WIRING DUCT
extra long description	PAN G3X2LG6 Panduct [®] G3X2LG6 Base W
Long Description	The G3X2LG6 Panduct Lead-Free PVC Wide Slot Wiring Duct
	feature a wide slot/finger design that provides greater sidewall
	rigidity and is suitable with a range of wire bundle sizes. UL 94
	flame class of V-0 with a UL recognized continuous-use
	temperature up to 122°F (50°C). Mounting holes provided. 3.0" :
	2.0" (76.2. mm x 50.8 mm) and 6' (1.8 m) long. Cover sold
Droduct Typo	
Product Type	separately. Color Light Gray. Panduct® G3X2LG6 Base Wiring Duct



ELLIOT ELECTRIC SUPPLY No Deliver Cost Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	PANDUIT
GTIN	00074983545872
Manufacturers Part Number	G3X2LG6
UPC	074983545872
Taxonomies, Classifications, and Cate	egories
Category Description	WIRE DUCT AND COVERS
Туре	Base Wiring Duct
Packaging	
Carton	6
Package	120
Weight Per each	0.0166
Uses, Certifications, and Standards	
Application	Wide slot/finger design provides greater sidewall rigidity and can be used in a wide range of applications
standard	CSA Approved;RoHS Compliant, UL Recognized, CE Compliant