

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

GBB2R 2A 250VAC/125VDC Vfa 1/4X1-1/4" Rohs Fuse Bussmann Fuses

Catalog Number	GBB2R
Manufacturer	
Description	Eaton Agc Series Fast-Acting Fuse, 7A, 250 Vac, 32 VDC (Self
Weight per unit	
Product Category	Small Dimension Fuses
Features	
amperage rating	2 A
connection	Ferrule End X Ferrule End
dimensions	1.2500 IN X 0.2500 IN X 0.2500 IN
interrupt rating	200 AIC at 250 Vac10 kAIC at 125 Vac/dc
Material	Ceramic tubeNickel-plated brass end cap construction
Response Time	2 min at 150%, 1 sec at 250%
type of indicators	Non-Indicating
Voltage Rating	250 VAC, 125 VDC
Dimensions and Weight	
Size	1/4 In Diameter X 1-1/4 In Length
Descriptions	
Description	2A 250VAC/125VDC VFA 1/4X1-1/4" ROHS FUSE
extra long description	
Features	Very fast-acting, ceramic tube 1/4" x 1-1/4" ferrule fuse designed
	to UL 248-14 for overcurrent protection of sensitive electronic
	circuits. Install into a Bussmann Series fuse holder, block, or fuse
	clip or purchase with available axial leads for thru-hole
	installation. Eaton's GBB very fast-acting, ceramic tube 1/4" x
	1-1/4" ferrule fuses are designed to UL 248-14 for overcurrent
	protection of sensitive electronic circuits. Order in cartridge fuse
	format and install into a Bussmann Series fuse holder, b
Long Description	Eaton AGC series Fast-acting fuse, 7A, 250 Vac, 32 Vdc (self certified), R
Product Type	GBB 2A Buss Fa 5-In Box -R
Special Features	Interrupt Rating 200 Amp at 250 Vac, 10000 Amp at 125 Vac/Vd Material Ceramic Tube, Nickel Plated Brass Endcap, ROHS Compliant



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712549912
Manufacturers Part Number	GBB-2-R
UPC	051712549912
Taxonomies, Classifications, and Cate	qories
	GLASS FUSES (and ceramic)
Туре	Very fast-acting fuse
Availability	
minimum qty	5
Packaging	
Carton	5
Weight Per each	0.01
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	RoHS Compliant,CE Marked