

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Carton

Weight Per each

GFEP250 Type BR 30 Ma GFI BRKR 50A/2 Pole 120/240V 10K Eaton Corp

Soon	
Catalog Number	GFEP250
Manufacturer	Eaton Corp
Description	Eaton BR Gfci Circuit Breaker, Industrial Ground Fault Thermal-Magnetic Equipment Protector, 50 A, 10 Kaic, Two-Pole, 120/240 V, Gfep, Common, #14-4 Awg, Ground Fault Circuit Interrupter, GFI
Weight per unit	0.8000 (lbs/each)
Product Category	20190104134007
Features	
dimensions	5.7500 IN X 3.0000 IN X 4.5000 IN
interrupt rating	10
Poles	2
Voltage Rating	120/240 V
Descriptions	
Description	TYPE BR 30 MA GFI BRKR 50A/2 POLE 120/240V 10K
extra long description	ETN GFEP250 BR 30 mA GFI 50A/2 Pole
Features	Eaton's BR circuit breakers are used in indoor and outdoor BR loadcenters, spa panels, meter breakers and sub panels. They are designed for a wide range of applications such as high short-circuit interrupt, series rating combinations with upstream main breakers, thermal magnetic, AFCI, GFCI, equipment protection and dual function AF/GF.
Long Description	Eaton BR GFCI circuit breaker,Industrial ground fault thermal-magnetic equipment protector,50 A,10 kAIC,Two-pole,120/240 V,GFEP,Common,#14-4 AWG,Ground fault circuit interrupter,GFI
Product Type	BR 30 Ma GFI 50A/2 Pole 120/240V 10K
Manufacturer Information	
Brand	Eaton
GTIN	00786676092074
Manufacturers Part Number	GFEP250
UPC	786676092074
Taxonomies, Classifications, and C	Categories
	Fault Sensing Breakers (AFCI/GFCI)
Туре	GFCI circuit breakers
Packaging	
Corton	1

1

8.0

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

iuai us
OtherGeneration - Conventional Energy - Conventional
EnergyDatacenters - IT Space: CI and Hyper ConvergedMarine
Vessels and Equipment - Marine Vessels and Equipment -
OtherGeneration - Renewable Energy - Alternative Energy
UL 489