

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

GI A4 4-14 Lay-In Conn

| GLA4 4-14 Lay-In Nsi Industries | i Conn | | | |
|----------------------------------|---|--|--|--|
| Catalog Number | GLA4 | | | |
| Manufacturer | Nsi Industries | | | |
| Description | Lay-In Connector, #14 Awg Conductor Size, #4 Awg Conductor Size, Non-Insulated, Aluminum/Copper Conductor Material, +90 °C Operating Temperature, 1.07 In Overall Length, 600 V Ac, 0.02 LB/Ea | | | |
| Weight per unit | 0.0200 (lbs/each) | | | |
| Product Category | Large Terminals & Connectors | | | |
| Features | | | | |
| Material | Aluminum | | | |
| Number of Conductors | 1 | | | |
| Poles | 1 | | | |
| Voltage Rating | | | | |
| Warranty | | | | |
| Wire Size | | | | |
| Wire Type | AL/C: | | | |
| Material, Color, and Finish | | | | |
| Color | Aluminum | | | |
| Finish | Tin-Plated | | | |
| Dimensions and Weight | | | | |
| Size | L=1.07 - H=.750 - W=.380 | | | |
| Descriptions | | | | |
| Description | 4-14 LAY-IN CONN | | | |
| extra long description | NSI GLA-4 AL Lay In Connector 4-14 | | | |
| Features | Lay In Connector 4 - 14 AWG Lay-in connectors offer the ultimate in flexibility. Excellent for grounding and continuous loop applications. Made of 6061T-6 aluminum alloy. Electro-tin plated for low contact resistance. Suitable for use with both copper and aluminum conductors. Rated 600V (2000V max. per UL486B). UL 486A/B Listed. Temperature rating 90 degrees C. | | | |
| Manufacturer Information | | | | |
| GTIN | 00662381001900 | | | |
| UPC | 662381001900 | | | |
| Taxonomies, Classifications, and | l Categories | | | |
| Category Description | Comp & Mech Lugs and Butt Splices | | | |

Aluminum Lay-In Lug



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost. Quality Products. & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| VVC DCIIVCILOWCI | Oost, | Quality i | roducts, & r | Craoriai Octivice |
|------------------|-------|-----------|--------------|-------------------|
| | | | | |
| | | | | |

| 100 |
|------------------|
| 0.02 |
| |
| Wire Termination |
| 90 C |
| UL486A/B |
| 90 C |
| |