

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Туре

## GUAT24 3/4" Guat Cond Body&CVR Crouse-Hinds

Catalog Number	GUAT24
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Gua Conduit Outlet Box With Cover, 2" Cover Opening Diameter, Feraloy Iron Alloy, T Shape, 3/4"
Weight per unit	1.8 (lbs/each)
Product Category	Bodies & Covers
Features	
Cable Entry	(3) Side
dimensions	4.2500 IN X 2.0000 IN X 3.3800 IN
Dimensions and Weight	
Size	3/4 in
Descriptions	
Construction	Explosionproof, Dust-Ignitionproof, Raintight
Description	3/4" GUAT COND BODY&CVR
extra long description	CRS-H GUAT24 3/4 OUTLET BX 2 CVR FO
Features	Crouse-Hinds series GUA and GUR explosionproof conduit outlet boxes are installed in conduit systems in hazardous areas to protect conductors in threaded rigid conduit, act as pull and splice boxes, change conduit direction, and provide access to conductors for maintenance and future system changes. GUA and GUR outlet boxes are certified for Class I, Division 1, Groups B, C, D and Class II, Division 1, Groups E, F, G. GUA boxes are available in ten different hub arrangements, maximizing flexibility in th
Long Description	Eaton Crouse-Hinds series Condulet GUA conduit outlet box with cover, 2" cover opening diameter, Feraloy iron alloy, T shape, 3/4"
Product Type	3/4 Outlet BX 2 CVR For THRD Rigid/Imc
Special Features	With Cover, Cover Opening Diameter 2 In
Vanufacturer Information	
Brand	Eaton
GTIN	00782274467405
Manufacturers Part Number	GUAT24
UPC	782274467405
Taxonomies, Classifications, and Category Description	Categories HUB STYLE BOXES (GUAB, GUAT, ETC)
_	

Conduit outlet box with cover



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Packaging

Carton	2
Weight Per each	1.83
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 886, CSA C22.2