



3M™ Highland™

Electrical Spring Connectors

Data Sheet

Application

Use the 3M™ Highland™ Electrical Spring Connectors to electrically connect two or more wire ends in a pigtail application and insulate the connection. The wire range shall be 22 thru 10 AWG solid or stranded copper wire.

Construction

Spring—Steel, plated
Insulator—Vinyl

Engineering Specification

The Highland Electrical Spring Connectors shall be capable of connecting two or more wires in a pigtail application, in the wire range of No. 22 thru No. 10 solid or stranded copper conductors. The connectors shall be constructed of a plated steel spring, covered by a vinyl insulator. The connectors shall be UL Listed and CSA Certified.

Regulatory Agencies

UL Listed as a Pressure Cable Connector

Tested per UL Standard 486C

UL File No. E23438

CSA Certified as a Pressure Cable Connector

Tested to CSA Standard C22.2

No. 0,188-M1983

CSA File No. 58960

Specifications

Max. Voltage rating

300V or 600V Building Wire

1000V Signs, Lighting Fixtures and Luminaries

Max temperature rating

105°C (221°F)-UL

For Regulatory information including RoHS, REACH, please www.3m.com/regs

Installation Instructions

WARNING

Working around energized systems may cause serious injury or death. Installation should be performed by personnel familiar with good safety practice in handling electrical equipment. De-energize and ground all electrical systems before installing product.

CAUTION: Turn power off before installing or removing connector. All electrical work should be done according to appropriate electrical codes.

1. Strip the wire insulation according to the strip lengths in the package instructions.
2. Firmly grasp wires, making sure insulation ends are even and tightly bundled. (Wires may be twisted or untwisted.) Lead stranded wires slightly. Slip the connector over wire tips.
3. Turn connector onto wires in clockwise direction until secure. Pull each conductor moderately to confirm that they are firmly secured.

**Metric wire combinations (copper only)
not UL Listed or CSA Certified.**

Size	H-29 Gray	H-30 Blue	H-31 Orange	H-33 Yellow	H-35 Red
0,50 mm2	3 to 5	3 to 5			
0,75 mm2	2 to 3	2 to 4	3 to 5	3 to 6	-
1,0 mm2	2	2 to 3	2 to 4	2 to 5	5 to 6
1,5 mm2	-	2	2 to 3	3 to 4	3 to 6
2,5 mm2		-		2 to 3	2 to 5
4 mm2		-			2 to 4

Wire combination

Solid or stranded copper conductors only

H-29 (Gray) (300 Volts)	H-30 (Blue) (300 Volts)	H-35 (Red) (600 Volts)
3 to 5 No. 22	5 No. 22	3 to 9 No. 18
2 to 4 No. 20	3 to 5 No. 20	2 to 6 No. 14
2 or 3 No. 18	2 to 4 No. 18	2 to 4 No. 12
2 No. 16	2 or 3 No. 16	2 to 3 No. 10
1 No. 20 w/ 1 to 4 No. 22	1 No. 20 w/ 4 No. 22	2 No. 14 w/ 1 to 4 No. 18
2 No. 20 w/ 1 to 3 No. 22	2 No. 20 w/ 2 or 3 No. 22	2 No. 14 w/ 1 to 4 No. 16
3 No. 20 w/ 1 or 2 No. 22	3 No. 20 w/ 1 or 2 No. 22	3 No. 14 w/ 1 to 3 No. 16
1 No. 18 w/ 1 No. 20 w/ 1 No. 22	4 No. 20 w/ 1 No. 22	3 No. 14 w/ 1 to 3 No. 18
1 No. 18 w/ 1 to 4 No. 22	1 No. 18 w/ 2 to 4 No. 20	4 No. 14 w/ 1 to 2 No. 16
1 No. 18 w/ 1 or 2 No. 20	1 No. 18 w/ 3 or 4 No. 22	4 No. 14 w/ 1 to 2 No. 18
2 No. 18 w/ 1 No. 20 or No. 22	1 or 2 No. 18 w/ 1 No. 20 w/ 1 No. 22	5 No. 14 w/ 1 No. 16
1 No. 16 w/ 1 No. 18 or No. 22	2 No. 18 w/ 1 to 3 No. 20	5 No. 14 w/ 1 No. 18
H-31 (Orange)(600 Volts)	2 No. 18 w/ 1 to 3 No. 22	1 No. 12 w/ 1 to 4 No. 18
5 No. 22	3 No. 18 w/ 1 or 2 No. 20 or No. 22	1 No. 12 w/ 1 to 4 No. 16
3 to 5 No. 20	4 No. 18 w/ 1 No. 22	1 No. 12 w/ 1 to 5 No. 14
2 to 5 No. 18	1 No. 16 w/ 1 to 4 No. 20	2 No. 12 w/ 1 to 3 No. 16
2 to 3 No. 16	1 No. 16 w/ 1 to 4 No. 22	2 No. 12 w/ 1 to 3 No. 18
2 No. 14	1 No. 16 w/ 1 or 2 No. 18	2 No. 12 w/ 1 to 4 No. 14
1 No. 16 w/ 1 to 4 No. 18	2 No. 16 w/ 1 to 3 No. 22	3 No. 12 w/ 1 to 2 No. 16
2 No. 16 w/ 1 or 2 No. 18	2 No. 16 w/ 1 or 2 No. 20	3 No. 12 w/ 1 to 2 No. 18
1 No. 14 w/ 1 to 3 No. 18	2 No. 16 w/ 1 No. 18	3 No. 12 w/ 2 or 3 No. 14
1 No. 14 w/ 1 or 2 No. 16	1 No. 14 w/ 1 to 4 No. 22	4 No. 12 w/ 1 No. 14
2 No. 14 w/ 1 to 3 No. 20 or No. 22	1 No. 14 w/ 1 to 3 No. 20	4 No. 12 w/ 1 No. 16
H-33 (Yellow) (600V)	1 No. 14 w/ 1 No. 16	4 No. 12 w/ 1 No. 18
4 or 5 No. 22	1 No. 14 w/ 1 No. 18	1 No. 10 w/ 1 to 3 No. 12
3 to 5 No. 20		1 No. 10 w/ 1 to 3 No. 14
2 to 7 No. 18		2 No. 10 w/ 1 to 3 No. 18
2 to 4 No. 16		2 No. 10 w/ 1 to 3 No. 16
2 to 3 No. 14		2 No. 10 w/ 1 or 2 No. 14
2 No. 12		2 No. 10 w/ 1 or 2 No. 12
2 No. 18 w/ 2 to 4 No. 16		
1 or 2 No. 16 w/ 1 to 3 No. 18		
1 No. 14 w/ 1 to 4 No. 16		
1 No. 14 w/ 1 to 3 No. 18		
2 No. 14 w/ 1 to 2 No. 16		



is a trademark of Underwriters Laboratories.



is a trademark of Canadian Standards Association

3M and Highland are trademarks of 3M

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com



Electrical Markets Division

6801 River Place Blvd.

Austin, TX 78726-9000

Phone: 800.245.3573

www.3M.com/electrical

Printed in USA

© 3M 2021. All Rights Reserved

80-6108-5288-3 Rev B



3M™ Highland™

Electrical Spring Connectors

Data Sheet

Application

Use the 3M™ Highland™ Electrical Spring Connectors to electrically connect two or more wire ends in a pigtail application and insulate the connection. The wire range shall be 22 thru 10 AWG solid or stranded copper wire.

Construction

Spring—Steel, plated
Insulator—Vinyl

Engineering Specification

The Highland Electrical Spring Connectors shall be capable of connecting two or more wires in a pigtail application, in the wire range of No. 22 thru No. 10 solid or stranded copper conductors. The connectors shall be constructed of a plated steel spring, covered by a vinyl insulator. The connectors shall be UL Listed and CSA Certified.

Regulatory Agencies

UL Listed as a Pressure Cable Connector

Tested per UL Standard 486C

UL File No. E23438

CSA Certified as a Pressure Cable Connector

Tested to CSA Standard C22.2

No. 0,188-M1983

CSA File No. 58960

Specifications

Max. Voltage rating

300V or 600V Building Wire

1000V Signs, Lighting Fixtures and Luminaries

Max temperature rating

105°C (221°F)-UL

For Regulatory information including RoHS, REACH, please www.3m.com/regs

Installation Instructions

WARNING

Working around energized systems may cause serious injury or death. Installation should be performed by personnel familiar with good safety practice in handling electrical equipment. De-energize and ground all electrical systems before installing product.

CAUTION: Turn power off before installing or removing connector. All electrical work should be done according to appropriate electrical codes.

1. Strip the wire insulation according to the strip lengths in the package instructions.
2. Firmly grasp wires, making sure insulation ends are even and tightly bundled. (Wires may be twisted or untwisted.) Lead stranded wires slightly. Slip the connector over wire tips.
3. Turn connector onto wires in clockwise direction until secure. Pull each conductor moderately to confirm that they are firmly secured.

**Metric wire combinations (copper only)
not UL Listed or CSA Certified.**

Size	H-29 Gray	H-30 Blue	H-31 Orange	H-33 Yellow	H-35 Red
0,50 mm2	3 to 5	3 to 5			
0,75 mm2	2 to 3	2 to 4	3 to 5	3 to 6	-
1,0 mm2	2	2 to 3	2 to 4	2 to 5	5 to 6
1,5 mm2	-	2	2 to 3	3 to 4	3 to 6
2,5 mm2		-		2 to 3	2 to 5
4 mm2		-			2 to 4

Wire combination

Solid or stranded copper conductors only

H-29 (Gray) (300 Volts)	H-30 (Blue) (300 Volts)	H-35 (Red) (600 Volts)
3 to 5 No. 22	5 No. 22	3 to 9 No. 18
2 to 4 No. 20	3 to 5 No. 20	2 to 6 No. 14
2 or 3 No. 18	2 to 4 No. 18	2 to 4 No. 12
2 No. 16	2 or 3 No. 16	2 to 3 No. 10
1 No. 20 w/ 1 to 4 No. 22	1 No. 20 w/ 4 No. 22	2 No. 14 w/ 1 to 4 No. 18
2 No. 20 w/ 1 to 3 No. 22	2 No. 20 w/ 2 or 3 No. 22	2 No. 14 w/ 1 to 4 No. 16
3 No. 20 w/ 1 or 2 No. 22	3 No. 20 w/ 1 or 2 No. 22	3 No. 14 w/ 1 to 3 No. 16
1 No. 18 w/ 1 No. 20 w/ 1 No. 22	4 No. 20 w/ 1 No. 22	3 No. 14 w/ 1 to 3 No. 18
1 No. 18 w/ 1 to 4 No. 22	1 No. 18 w/ 2 to 4 No. 20	4 No. 14 w/ 1 to 2 No. 16
1 No. 18 w/ 1 or 2 No. 20	1 No. 18 w/ 3 or 4 No. 22	4 No. 14 w/ 1 to 2 No. 18
2 No. 18 w/ 1 No. 20 or No. 22	1 or 2 No. 18 w/ 1 No. 20 w/ 1 No. 22	5 No. 14 w/ 1 No. 16
1 No. 16 w/ 1 No. 18 or No. 22	2 No. 18 w/ 1 to 3 No. 20	5 No. 14 w/ 1 No. 18
H-31 (Orange)(600 Volts)	2 No. 18 w/ 1 to 3 No. 22	1 No. 12 w/ 1 to 4 No. 18
5 No. 22	3 No. 18 w/ 1 or 2 No. 20 or No. 22	1 No. 12 w/ 1 to 4 No. 16
3 to 5 No. 20	4 No. 18 w/ 1 No. 22	1 No. 12 w/ 1 to 5 No. 14
2 to 5 No. 18	1 No. 16 w/ 1 to 4 No. 20	2 No. 12 w/ 1 to 3 No. 16
2 to 3 No. 16	1 No. 16 w/ 1 to 4 No. 22	2 No. 12 w/ 1 to 3 No. 18
2 No. 14	1 No. 16 w/ 1 or 2 No. 18	2 No. 12 w/ 1 to 4 No. 14
1 No. 16 w/ 1 to 4 No. 18	2 No. 16 w/ 1 to 3 No. 22	3 No. 12 w/ 1 to 2 No. 16
2 No. 16 w/ 1 or 2 No. 18	2 No. 16 w/ 1 or 2 No. 20	3 No. 12 w/ 1 to 2 No. 18
1 No. 14 w/ 1 to 3 No. 18	2 No. 16 w/ 1 No. 18	3 No. 12 w/ 2 or 3 No. 14
1 No. 14 w/ 1 or 2 No. 16	1 No. 14 w/ 1 to 4 No. 22	4 No. 12 w/ 1 No. 14
2 No. 14 w/ 1 to 3 No. 20 or No. 22	1 No. 14 w/ 1 to 3 No. 20	4 No. 12 w/ 1 No. 16
H-33 (Yellow) (600V)	1 No. 14 w/ 1 No. 16	4 No. 12 w/ 1 No. 18
4 or 5 No. 22	1 No. 14 w/ 1 No. 18	1 No. 10 w/ 1 to 3 No. 12
3 to 5 No. 20		1 No. 10 w/ 1 to 3 No. 14
2 to 7 No. 18		2 No. 10 w/ 1 to 3 No. 18
2 to 4 No. 16		2 No. 10 w/ 1 to 3 No. 16
2 to 3 No. 14		2 No. 10 w/ 1 or 2 No. 14
2 No. 12		2 No. 10 w/ 1 or 2 No. 12
2 No. 18 w/ 2 to 4 No. 16		
1 or 2 No. 16 w/ 1 to 3 No. 18		
1 No. 14 w/ 1 to 4 No. 16		
1 No. 14 w/ 1 to 3 No. 18		
2 No. 14 w/ 1 to 2 No. 16		



is a trademark of Underwriters Laboratories.



is a trademark of Canadian Standards Association

3M and Highland are trademarks of 3M

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com



Electrical Markets Division

6801 River Place Blvd.

Austin, TX 78726-9000

Phone: 800.245.3573

www.3M.com/electrical

Printed in USA

© 3M 2021. All Rights Reserved

80-6108-5288-3 Rev B