

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



**UPC** 

## HBL2325SW LKG WT S/SHRD FLG-InIt, 20A 250V, L6-20P Hubbell Wiring Devices

Catalog Number	HBL2325SW
Manufacturer	Hubbell Wiring Devices
Description	Watertight Safety-Shroud®, Locking Devices, Twist-Lock®, Flanged Inlet, 20A 250V Ac, 2-Pole 3-Wire Grounding, Nema L6-20P, Screw Terminal, Gray.
Weight per unit	
Product Category	Plugs, Connectors, Inlets, Out
eatures	
amperage rating	20
connection	Screw Terminals
Current Rating	20
Dielectric Strength	Withstands 2,000V minimum
insulation	
Number of Wires	3-Wire
Phase	1
Poles	2-Pole
Voltage Rating	250 V
Wattage	5,000
Wire Size	#16 to #8
imensions and Weight	
Size	3.75 in x 3.75 in x 2.28 in
escriptions	
Description	LKG WT S/SHRD FLG-INLT, 20A 250V, L6-20P
extra long description	HWDK HBL2325SW LKG WT S/SHRD FLG-IN
Long Description	Watertight Safety-Shroud®, Locking Devices, Twist-Lock®,
	Flanged Inlet, 20A 250V AC, 2-Pole 3-Wire Grounding, NEMA
	L6-20P, Screw Terminal, Gray.
Product Type	LKG WT S/SHRD FLG-InIt, 20A 250V, L6-20P
Special Features	Standard Product
lanufacturer Information	
Brand	WIRING DEVICE-KELLEMS
GTIN	00783585231143
Manufacturers Part Number	HBL2325SW

783585231143



standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	
Category Description	NEMA RATED TURNLOK PLUGS, CONNECTORS, & RECEPTICLES
Туре	Flanged Inlet
Packaging	
Carton	1
Package	5
Weight Per each	0.55
Uses, Certifications, and Standards	
Application	Extra Heavy Duty Industrial
environmental conditions	Watertight
Mounting	Screw Mount
nema rating	L6-20P

UL Listed, CSA Certified To Type 4, 4X And Type 12