

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### HBL5666C Plug, 15A 250V, 6-15P, B/W Hubbell Wiring Devices

Catalog Number	HBL5666C
Manufacturer	Hubbell Wiring Devices
Description	Straight Blade Devices, Male Plug, Insulgrip Heavy Duty,
	Industrial/Commercial Grade, Straight, 2-Pole 3- Wire Grounding,
	15A 250V, 6-15P, Black and White, Single Pack.
Weight per unit	0.0490 (lbs/each)
Product Category	Pluas, Connectors, Inlets, Out

#### **Features**

amperage rating	15
connection	Screwed Terminal
Cord Type	All Portable
	15
Material	COMPOSITE
Number of Wires	3-Wire
pallet quantity	6600
Phase	1
Poles	2-Pole
Valtage Deting	250
Mattaga	3
Wire Size	#18 AWG to #10 AWG

#### **Dimensions and Weight**

(170	7 in x 1.53 in x 1.53 in
------	--------------------------

### **Descriptions**

Description	PLUG, 15A 250V, 6-15P, B/W
extra long description	HWDK HBL5666C PLUG, 15A 250V, 6-15P
Long Description	Straight Blade Devices, Male Plug, Insulgrip Heavy Duty,
	Industrial/Commercial Grade, Straight, 2-Pole 3- Wire Grounding,
	15A 250V, 6-15P, Black and White, Single Pack.
Product Type	Plug, 15A 250V, 6-15P, B/W
Special Features	Standard Product

### **Manufacturer Information**

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585175607
Manufacturers Part Number	HBL5666C
series	Insulgrip®
UPC	783585175607



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

<b>Taxonomies</b>	, Classifications,	and C	ategories
-------------------	--------------------	-------	-----------

Category Description	Commercial cord connectors
	PLUG
Packaging	1
Carton	
Package	10
Weight Per each	0.049

#### **Uses, Certifications, and Standards**

Application	Industrial/Commercial
environmental conditions	Ribbed Nylon Housing Is Impact and Chemical Resistant
Mounting	Cord
nema rating	6-15P
standard	CSA Certified to C22.2 No. 42 File 280; NEMA® WD-6
	Compliant; UL Listed to UL498 File E1706