

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



HBL9452C Plug, Ang, 3P4W, 50A 125/250V, 14-50P Hubbell Wiring Devices

Catalog Number	HBL9452C
Manufacturer	Hubbell Wiring Devices
Description	Engineered Specifically For Ev Charging Applications, Hubbell'S 14-50P Straight Blade Angled Plug Stands Out As A Superior and Reliable Choice, Fully Compatible With Established Ev Charging Standards. This Sturdy Plug Is Crafted to Offer Exceptional Durability, Safety, and High Performance, Making It The Ideal Choice For Environments That Demand Reliability In Ev Power Delivery.
Weight per unit	0.8000 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out
eatures	
amperage rating	50
connection	Screwed Terminal
Cord Type	
Current Rating	50
Material	Nylon
Number of Wires	4-Wire
pallet quantity	765
Phase	
Poles	3-Pole
Voltage Rating	125;250
Wattage	12500
Wire Size	#12 to #4
imensions and Weight	
Size	4.5 in x 3.38 in x 2.37 in
escriptions	
Description	PLUG, ANG, 3P4W, 50A 125/250V, 14-50P
extra long description	HWDK HBL9452C PLUG, ANG, 3P4W, 50A
Long Description	Engineered specifically for EV charging applications, Hubbell's 14-50P straight blade angled plug stands out as a superior and reliable chaise. fully compatible with established EV charging
	reliable choice, fully compatible with established EV charging standards. This sturdy plug is crafted to offer exceptional durability, safety, and high performance, making it the ideal choice for environments that demand reliability in EV power delivery.
Product Type	Plug, Ang, 3P4W, 50A 125/250V, 14-50P
Special Features	Angled, 4-Position



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Hubbell Wiring Devices
GTIN	00783585015330
Manufacturers Part Number	HBL9452C
series	Extra Heavy Duty
UPC	783585015330
Taxonomies, Classifications, and C	ategories
	Residential receptacles
Туре	PLUG
Packaging	
Carton	
Package	
Weight Per each	0.8
Uses, Certifications, and Standards	5
Application	Industrial/Commercial
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Cord
nema rating	14-50P
standard	UL Listed To UL498 File E1706, CSA Certified To C22.2 No. 42 File 280