

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

HCLR15 15A 600V Class CC Fast Acting Fuse

Category Description MIDGET FUSES

FUSE

| Catalog Number | HCLR15 |
|---------------------------|--|
| Manufacturer | Edison Fuses |
| Description | Class CC Fuse, 15 A, 600 V Ac, Melamine (Body); Brass (End Cap) Material, 0.41 In Diameter, 1.50 In Overall Length, 0.02 LB |
| Weight per unit | 0.0200 (lbs/each) |
| Product Category | Renewable & Non-Renewable |
| atures | |
| amperage rating | 15 |
| class | 0100 |
| dimensions | 1.0000 IN X 0.4060 IN X 0.4060 IN |
| media | Yes |
| mensions and Weight | |
| Height | 0.406 |
| Length | 1 |
| Width | 0.406 |
| escriptions | |
| Description | 15A 600V CLASS CC FAST ACTING FUSE |
| extra long description | EFSE HCLR15 UL CLASS CC FAST ACTING |
| Features | Edison offers a complete line of Class CC fuses to meet your |
| | circuit and equipment protection needs. These branch circuit |
| | rated compact fuses rated 600v, and delivering 200,000a IR Vac |
| | Sym provide excellent protection in the smallest package of any |
| | UL class of fuses. Choose from our EDCC time-delay fuses for |
| | your small horsepower motor circuits, our HCLR fast-acting for |
| | your non-inductive lighting and resistance heating loads or our |
| | HCTR time-delay fuses for your small control transformer |
| Chariel Factures | protection. |
| Special Features | Rejection Style |
| anufacturer Information | |
| Brand | Eaton |
| GTIN | 00782634420705 |
| Manufacturers Part Number | T626-HCLR15 |
| UPC | 782634420705 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| U | 2 | $\boldsymbol{\sim}$ | v | 2 | a | | n | \sim |
|---|---|---------------------|---|---|---|---|---|--------|
| г | a | b | N | а | u | ı | | u |
| | | | | | J | | | J |

| Carton | 1 |
|-----------------|------|
| Package | 10 |
| Weight Per each | 0.02 |

Uses, Certifications, and Standards

| Application | Datacenters - Facilities: Critical Power |
|-------------|---|
| standard | UL Listed, CSA Certified, CE Marked, RoHS Compliant |