

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



HST1.1485Y Heat Shrink Tubing *Panduit Corporation*

Catalog Number	HST1.1485Y
Manufacturer	Panduit Corporation
Description	The HST1.1-48-5Y Thick Wall Heat Shrink Features An Adhesive Lined Inner Wall That Seals and Provides Excellent Protection Against Moisture. Applications Include Insulating and Protecting Wires/Cables In Outdoor, Wet Locations. Thick Wall For Direct Burial. Voltage Rating: UI 486D Listed For 600 V 90°C Continuous Use. Shrink Ratio: 3:1. Temperature Range: -67°F to 230°F (-55°C to 110°C). Cross-Linked Polyolefin. 1.1" (27.9 MM) Dia. 48" (1219.2 MM) Length. Color Black. 5 Per Package.
Weight per unit	2.8 (lbs/each)
Product Category	Insulating Materials
Features	
continuous operating temperat	230
flammability	VW-1
Inside Diameter	0.38
media	Yes
outside diameter	1.1
Shrink Ratio	3:1
Material, Color, and Finish Color	Black
	DIACK
Dimensions and Weight	0.12
Thickness	0.12
Descriptions	
Description	HEAT SHRINK TUBING
extra long description	PAN HST1.1-48-5Y Wet-Shrink™ HST1.1
Long Description	The HST1.1-48-5Y Thick Wall Heat Shrink features an adhesive lined inner wall that seals and provides excellent protection against moisture. Applications include insulating and protecting wires/cables in outdoor, wet locations. Thick wall for direct burial. Voltage rating: UL 486D Listed for 600 V 90°C continuous use. Shrink ratio: 3:1. Temperature range: -67°F to 230°F (-55°C to 110°C). Cross-linked Polyolefin. 1.1" (27.9 mm) dia. 48" (1219.2 mm) length. Color Black. 5 per package.
Product Type	Wet-Shrink™ HST1.1-48-5Y Heatshrink, BLK, Adh. Lined Po, 4'



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

M	anufac	turer In	forma	tion
---	--------	----------	-------	------

Brand	PANDUIT	
GTIN	00074983107315	
Manufacturers Part Number	HST1.1-48-5Y	
UPC	074983107315	

Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Туре	Heat-Shrink Tubing

Packaging

Carton	5
Weight Per each	2.75

Uses, Certifications, and Standards

For Wet Locations; Insulating and protecting wires and
cables;Suitable for direct burial
CSA: 244528;Mil Spec: AS23053;UL Listed: E173379;UL/UR:
E342365;UL224 VW-1