



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## HSTT1248Q2 HT Shrink Tubing *Panduit Corporation*

|                  |   |
|------------------|---|
| Catalog Number   | HSTT1248Q2  |
| Manufacturer     | Panduit Corporation   |
| Description      | Thin Wall Heat Shrink, .12" (3.2MM) Diameter, Red Cross-Linked Polyolefin, 25 PC. Package Quantity. |
| Weight per unit  | 1.0 (lbs/each)  |
| Product Category | Insulating Materials  |

### Features

|                  |                 |
|------------------|-----------------|
| flammability     | Flame Retardant |
| media            | Yes             |
| outside diameter | 0.125           |
| Shrink Ratio     | 2:1             |

### Material, Color, and Finish

|       |     |
|-------|-----|
| Color | Red |
|-------|-----|

### Dimensions and Weight

|           |      |
|-----------|------|
| Thickness | 0.02 |
|-----------|------|

### Descriptions

|                        |   |
|------------------------|---|
| Description            | HT SHRINK TUBING  |
| extra long description | PAN HSTT12-48-Q2 Dry-Shrink™ HSTT12   |
| Long Description       | Thin wall heat shrink, .12" (3.2mm) diameter, red cross-linked polyolefin, 25 pc. package quantity. |
| Product Type           | Dry-Shrink™ HSTT12-48-Q2 Heat Shrink  |

### Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | PANDUIT        |
| GTIN                      | 00074983906031 |
| Manufacturers Part Number | HSTT12-48-Q2   |
| UPC                       | 074983906031   |

### Taxonomies, Classifications, and Categories

|                      |                  |
|----------------------|------------------|
| Category Description | HEAT/COLD SHRINK |
|----------------------|------------------|

### Packaging

|                 |    |
|-----------------|----|
| Carton          | 25 |
| Weight Per each | 1  |

### Uses, Certifications, and Standards

|             |                                       |
|-------------|---------------------------------------|
| Application | For Dry Locations                     |
| standard    | UL Recognized, CSA Approved, MIL SPEC |