



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

HSTT1948Q Heatshrnk Tubing 3/16 BLK

Panduit Corporation

| | |
|------------------|---|
| Catalog Number | HSTT1948Q |
| Manufacturer | Panduit Corporation |
| Description | The HSTT19-48-Q Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Flame Retardant, Cross-Linked Polyolefin. 0.187" Diameter X 4' Long (4.8 MM X 1.2 M). Color Black. 25 Per Package. |
| Weight per unit | 0.8350 (lbs/each) |
| Product Category | Insulating Materials |

Features

| | |
|---------------------------------|-----------------|
| continuous operating temperatur | 275 |
| flammability | Flame Retardant |
| Inside Diameter | 0.093 |
| media | Yes |
| outside diameter | 0.187 |
| Shrink Ratio | 2:1 |

Material, Color, and Finish

| | |
|-------|-------|
| Color | Black |
|-------|-------|

Dimensions and Weight

| | |
|-----------|------|
| Thickness | 0.02 |
|-----------|------|

Descriptions

| | |
|------------------------|---|
| Description | HEATSHRNK TUBING 3/16 BLK |
| extra long description | PAN HSTT19-48-Q Dry-Shrink™ HSTT19- |
| Long Description | The HSTT19-48-Q Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 0.187" Diameter x 4' Long (4.8 mm x 1.2 m). Color Black. 25 per package. |
| Product Type | Dry-Shrink™ HSTT19-48-Q Heatshrink, Black, Po, 4' L, 0.187" |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | PANDUIT |
| GTIN | 00074983905904 |
| Manufacturers Part Number | HSTT19-48-Q |
| UPC | 074983905904 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|--------------------|
| Category Description | HEAT/COLD SHRINK |
| Type | Heat-Shrink Tubing |

Packaging

| | |
|-----------------|-------|
| Carton | 25 |
| Weight Per each | 0.835 |

Uses, Certifications, and Standards

| | |
|-------------|--|
| Application | For Dry Locations;Insulating and protecting wires and cables |
| standard | Mil Spec: AMS-DTL-23053/5 Class 1;UL: E122770 |