



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



HSTT1948Q Heatshrink Tubing 3/16 BLK *Panduit Corporation*

Catalog Number	HSTT1948Q
Manufacturer	Panduit Corporation
Description	The HSTT19-48-Q Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Flame Retardant, Cross-Linked Polyolefin. 0.187" Diameter X 4' Long (4.8 MM X 1.2 M). Color Black. 25 Per Package.
Weight per unit	0.8350 (lbs/each)
Product Category	Insulating Materials

Features

continuous operating temperat	275
flammability	Flame Retardant
Inside Diameter	0.093
media	Yes

Material, Color, and Finish

Color	Black
-------	-------

Descriptions

Description	HEATSHRNK TUBING 3/16 BLK
extra long description	PAN HSTT19-48-Q Dry-Shrink™ HSTT19-
Long Description	The HSTT19-48-Q Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 0.187" Diameter x 4' Long (4.8 mm x 1.2 m). Color Black. 25 per package.
Product Type	Dry-Shrink™ HSTT19-48-Q Heatshrink, Black, Po, 4' L, 0.187"

Manufacturer Information

Brand	PANDUIT
GTIN	00074983905904
Manufacturers Part Number	HSTT19-48-Q
UPC	074983905904



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description HEAT/COLD SHRINK

Packaging

Carton 25

Weight Per each 0.835

Uses, Certifications, and Standards

Application For Dry Locations; Insulating and protecting wires and cables