



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



HUB250DN 2-1/2" Rigid Watertite Die Cast Hub

Appleton/Oz Gedney

| | |
|------------------|---|
| Catalog Number | HUB250DN |
| Manufacturer | Appleton/Oz Gedney |
| Description | Watertight Hubs, Zinc Diecast Hubs - Insulated, Class I, Div 2, Trade Size: 2-1/2", Body Length: 1.56", Thread Length: 1.06", Outside Diameter: 3.72" |
| Weight per unit | 1.7 (lbs/each) |
| Product Category | Rigid Conduit Fittings - Steel |

Features

| | |
|----------|---------------|
| Material | Zinc Die Cast |
|----------|---------------|

Dimensions and Weight

| | |
|------|-------|
| Size | 2-1/2 |
|------|-------|

Descriptions

| | |
|------------------------|---|
| Description | 2-1/2" RIGID WATERTITE DIE CAST HUB |
| extra long description | EGS HUB250DN 2-1/2 ZDC WATER LIGHT |
| Long Description | Watertight Hubs, Zinc Diecast Hubs - Insulated, Class I, Div 2, Trade Size: 2-1/2", Body Length: 1.56", Thread Length: 1.06", Outside Diameter: 3.72" |
| Product Type | 2-1/2 ZDC Water Light Hubs |
| Special Features | 2-1/2 IN Trade Size Hub, Hole Dia. Min 2.86 IN, Hole Dia. Max 3.00 IN, Panel Thickness Min. 0.06 IN, Panel Thickness Max. 0.31 IN, Insulated Throat |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | APPOZGCOMM |
| GTIN | 00687855002177 |
| Manufacturers Part Number | HUB250DN |
| UPC | 687855002177 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|--|
| Category Description | Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS AND THREADLESS CONNECTOR |
| Type | Watertight Hubs |

Packaging

| | |
|-----------------|------|
| Carton | 5 |
| Package | 25 |
| Weight Per each | 1.74 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Used to Connect Rigid or IMC Conduit to a Threadless Opening in an Enclosure

standard

CSA Certified: 065178; CSA Standard: C22.2 No. 18.3; NEMA: FB-1; UL Listed: E14814; UL Standard: 514B