

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Size

ISPB3503 350MCM-12AWG, 3PRT Ped Conn Nsi Industries

Catalog Number	ISPB3503
Manufacturer	Nsi Industries
Description	The Polaris ISPB350-3 Multi-Tap Direct Burial Single-Sided Entry Connector Features 3 Ports Sized For 350 MCM - 12 Awg Wires. The Body Is Made From Aluminum Alloy Wrapped In A Layer Of High-Dielectric Strength Rubber Insulation. Each Single-Sided Port Is Pre-Loaded With An Oxide Inhibitor, With Removable Access Plugs Over The Hex Screws Used to Tighten The Radial-Tipped Set Screws. Rated For Temporary Submersion, Wet or Damp Locations and Direct Burial Applications. Installs With A Hex Key and Torque Wrenc
Weight per unit	0.7300 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
Material	Aluminum
Number of Conductors	3
Poles	1
Voltage Rating	600 V
Warranty	1 YEAR
Wire Size	350 MCM-12 AWG
Wire Type	Class B & C
Material, Color, and Finish Finish	Plastisol
Dimensions and Weight	

L=3.610 - W=4.190 - H=3.060



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions	
Description	350MCM-12AWG,3PRT PED CONN
extra long description	NSI ISPB350-3 POLARIS EDGE Connecto
Features	The Polaris ISPB350-3 3-Port Single-Sided Submersible Connector
	provides the simplest solution for forming a secure connection between up to three conductors in direct burial or temporary
	submersal applications with a wide range of wire sizes. Sized for
	350 MCM - 12 AWG wires and rated for 600V, this pre-insulated
	connector comes pre-loaded with an oxide inhibitor and installs
	faster than traditional uninsulated connector options using just a
	hex key and torque wrench. The aluminum alloy body is wrapped
Long Description	in The Polaris ISPB350-3 Multi-Tap Direct Burial Single-Sided Entry
Long Description	Connector features 3 ports sized for 350 MCM - 12 AWG wires.
	The body is made from aluminum alloy wrapped in a layer of
	high-dielectric strength rubber insulation. Each single-sided port
	is pre-loaded with an oxide inhibitor, with removable access
	plugs over the hex screws used to tighten the radial-tipped set
	screws. Rated for temporary submersion, wet or damp locations and direct burial applications. Installs with a hex key and torque
	wrenc
Product Type	Polaris Edge Connector 350 3 Port BLK
Special Features	(3) 350 MCM-12 AWG - Dual Rated
Manufacturer Information	
Brand	Polaris
GTIN	00662381788955
Manufacturers Part Number	ISPB350-3
UPC	662381788955
Taxonomies, Classifications, and Cate	
Category Description	
Туре	Submersible Pedestal Connectors
Packaging	
Carton	
Weight Per each	0.73
Uses, Certifications, and Standards	Mr. +
Application	Wire Termination
environmental conditions	90 C
standard	•
Temperature Rating	90 C