


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





ITG30 3/0-#4 Polaris Insul-Tap Connector For Dlo Cable *Nsi Industries*

and the second second	
Catalog Number	ITG30
Manufacturer	Nsi Industries
Description	Multi-Tap Connector, #4 Awg Conductor Size, 3/0 Awg Conductor Size, Insulated, Plastisol Insulation Material, Copper Conductor Material, Gray Insulation Color, 2 Conductors, -45 °C Operating Temperature, +90 °C Operating Temperature, 1.85 In Overall Length, 600 V Ac, 0.19 LB/Ea
Weight per unit	0.1900 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
Material	Aluminum
Number of Conductors	2
Poles	1
Voltage Rating	600 V
Warranty	
Wire Size	
Wire Type	
Material, Color, and Finish	
Color	Grey
Finish	Diactical Inculated
Dimensions and Weight	
Size	L=1.850 - W=1.600 - H=1.810
Descriptions	
Description	3/0-#4 POLARIS INSUL-TAP CONNECTOR FOR DLO CABLE
extra long description	NSI ITG-3/0 POLARIS Grey Multi-Tap
Features	The Polaris ITG-3/0 2-Port Single-Side Connector provides the
	simplest solution for forming a secure connection between two
	fine-stranded wire conductors in applications including cable
	trays, troughs, wire-ways, raceways, ducts and motor junction
	boxes. Sized for 3/0 - 4 AWG wires and rated for 600V, this
	pre-insulated connector comes pre-loaded with an oxide
	inhibitor and installs faster than traditional uninsulated
	connector options using just a hex key and torque wrench. The
	aluminum alloy body is wrap
Manufacturer Information	
GTIN	00662381951533
UPC	662381951533



Temperature Rating

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

90 C

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	gories
Category Description	SPLIT BOLTS
Туре	Multi Cable
Packaging	
Carton	3
Package	6
Weight Per each	0.19
Uses, Certifications, and Standards	
Application	Wire Termination
environmental conditions	90 C
standard	UL 486A/B