

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



JDL10 10A 600V Class J Time Delay Fuse Edison Fuses

Catalog Number	JDL10
Manufacturer	Edison Fuses
Description	Eaton Edison Series JDL Fuse, Time-Delay Current-Limiting Fuse, Non-Indicating, 10 A, Class J, 200 Kaic, Standard, 10, 600 V
Weight per unit	0.0900 (lbs/each)
Product Category	Dual Element

Features

amperage rating	10 A
amps	10
class	Class J
dimensions	2.2500 IN X 0.8100 IN X 0.8100 IN
Fuse Type	Class J Time Delay Fuses
interrupt rating	200 kAIC
media	Yes
Voltage	600V
Voltage Rating	600 V

Descriptions

Description

Description	TOA GOOV GLASS S THIVE DELAT I OSE
extra long description	MOR T626-JDL10 Class J Time Delay F
Features	Edison's UL Class J fuse products are offered in both Dual-Element Time-Delay (JDL) and Fast-Acting (JFL) types. Both types have 200,000 amp interrupting rating at 600Vac RMS Sym amps. Their small physical size and high performance characteristics makes Class J fuses ideal for any space-limited applications. Edison's JFL fuses are best suited for the protection of non-inductive loads such as resistive heating and lighting circuits.
Long Description	Eaton Edison series JDL fuse, Time-delay current-limiting fuse, Non-indicating, 10 A, Class J, 200 kAIC, Standard, 10, 600 V
Product Type	Class J Time Delay Fuses 600V 10a
Special Features	Non-Indicating

10A 600V CLASS LTIME DELAY FUSE

Manufacturer Information

Brand	Eaton
GTIN	00782634803362
Manufacturers Part Number	JDL10
UPC	782634803362



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories		
Category Description	Fusas 8. Fusa Accassarias	
Туре	FUSE	
Packaging		
Carton	1	
Package	10	
Maight Dar each	0.09	
Uses, Certifications, and Standards		
Application	Datacenters - Facilities: Critical Power	

UL Listed, CSA Certified, CE Marked, RoHS Compliant