

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



JLLS60 60A 600V Vfa Class T Fuse Littelfuse

Catalog Number	JLLS60
Manufacturer	Littelfuse
Description	Space-Saving Class T Fuses Are The Most Compact Fuses Available In Ratings Above 30 Amperes — Less Than One-Third The Size Of Comparable Class R Fuses. When Rated In Accordance With The Nec, Class T Fuses Provide Fast-Acting Overload and Short Circuit Protection For Non-Inductive Circuits and Equipment. Used In Inductive Circuits, The Ampere Rating Of Class T Fuses Must Be Increased to Prevent Opening On Inrush Currents. In Such Instances, Class T Fuses May Provide Only Short Circuit Protection. For Motor
Weight per unit	0.0800 (lbs/each)
Product Category	Current Limiting
Features	
amperage rating	60
interrupt rating	0001.4
Response Time	
Voltage Rating	400 400
Dimensions and Weight	
Size	1.56L;1.0D
Descriptions	
Description	60A 600V VFA CLASS T FUSE
extra long description	LFSE JLLS060.T FUS 600V F/A CLASS T
Long Description	Space-saving Class T fuses are the most compact fuses available in ratings above 30 amperes — less than one-third the size of comparable Class R fuses. When rated in accordance with the NEC, Class T fuses provide fast-acting overload and short circuit protection for non-inductive circuits and equipment. Used in inductive circuits, the ampere rating of Class T fuses must be increased to prevent opening on inrush currents. In such instances, Class T fuses may provide only short circuit protection. For motor
Product Type	Fus 600V F/A Class T 60a
Special Features	Current-limiting



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

NASSI	ufacture	Y INTAK	'MASTIAM
IVIALII	1141111	<u>.</u> ,	1114116111
IVIGII	aiuctai t	,, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	HILLION

Brand	Littelfuse
GTIN	00079458190786
Manufacturers Part Number	JLLS060.T
UPC	079458190786

Taxonomies, Classifications, and Categories

Category Description	MIDGET FUSES
Туре	CLASS T

Packaging

Carton	1	
(A.71), (A.71)		
Weight Per each	0.08	

Uses, Certifications, and Standards

Application	Variable Speed Drives
Mounting	Ferrule
standard	248-15 Class T