

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## KA8C 14-8 Cu Lug ST SCH 1H Burndy LLC

| _                                    |   |
|--------------------------------------|---|
| Catalog Number                       | KA8C  |
| Manufacturer                         | Burndy LLC  |
| Description                          | Copper Terminal, 1 Hole, 14 Awg (Sol)-8 Awg (STR), #10 Stud, 1 Screw.   |
| Weight per unit                      | 0.0130 (lbs/each)   |
| Product Category                     | Large Terminals & Connectors  |
| Features                             |   |
| Material                             | Copper  |
| Descriptions                         |   |
| Description                          | 14-8 CU LUG ST SCH 1H   |
| extra long description               | BUR KA8C 14-8 CU LUG ST SCR 1H  |
| Long Description                     | Copper Terminal, 1 Hole, 14 AWG (Sol)-8 AWG (Str), #10 Stud, 1 Screw.   |
| Product Type                         | Terminal  |
| Special Features                     | Features: Compact, Economical, High Copper Alloy Terminal For<br>Joining A Wide Range Of Cable To Equipment Pads Or Terminal<br>Blocks, Dimension T: 3/32 IN, Dimension N: 3/16 IN, Dimension K:<br>7/32 IN, Tongue Width: 3/8 IN, Installation Torque: 25 IN-LB,<br>Length: 13/16 IN, Stud/bolt Hole Size: #10, Height: 5/8 IN |
| Manufacturer Information             |   |
| Brand                                | BURNDY  |
| GTIN                                 | 00781810362051  |
| Manufacturers Part Number            | KA8C  |
| UPC                                  | 781810362051  |
| Taxonomies, Classifications, and Car | tegories  |
| Category Description                 |   |
| Туре                                 | Bolted Lugs & Terminals   |
| Packaging                            |   |
| Carton                               | 1   |
| Package                              | 100   |
| Weight Per each                      | 0.013   |
| Uses, Certifications, and Standards  |   |
| Application                          | For Joining A Wide Range Of Copper Cable To Equipment Pads Or Terminal Blocks   |
| standard                             | UL 486A-486B  |
|                                      |   |