

Locking devices

Complex environment locking devices

Product description

3-pole, 4-wire grounding
30A, 125/250V/AC
NEMA L14-30




L14-30R L14-30P




CRL1430P



CRL1430C



CRL1430R



L1430RW

Dimensional information:
D-34-35

Specification information:
Watertight industrial plugs & connectors: D-38
Watertight industrial receptacles: D-39
Severe duty industrial plugs & connectors: D-40
Corrosion resistant: D-41

Plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
30	125/ 250	L14-30	Watertight	0.43-1.15" (10.9-29.2mm)	Y	<input type="checkbox"/> L1430PW	<input type="checkbox"/> L1430CW		
			Watertight	0.43-1.15" (10.9-29.2mm)	BK	<input type="checkbox"/> L1430PWBK	<input type="checkbox"/> L1430CWBK		
			Severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	<input type="checkbox"/> L1430PY	<input type="checkbox"/> L1430CY		
			Safety grip corrosion resistant	0.63-1.16" (15.9-29.4mm)	Y	<input type="checkbox"/> CRL1430P	<input type="checkbox"/> CRL1430C		

Receptacles


Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.		
30	125/ 250	L14-30	Watertight	Y	<input type="checkbox"/> L1430RW		
			Watertight	BK	<input type="checkbox"/> L1430RWBK		
			Corrosion resistant	Y	<input type="checkbox"/> CRL1430R*		

* Only UL Listed, CSA certified and Fed Spec certified

Complex environment locking devices

Product description

3-pole, 4-wire grounding
30A, 3Ø 250V/AC
NEMA L15-30



L15-30R L15-30P

3Ø plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
30	250	L15-30	3Ø watertight	0.43-1.15" (10.9-29.2mm)	Y	<input type="checkbox"/> L1530PW	<input type="checkbox"/> L1530CW		
			3Ø watertight	0.43-1.15" (10.9-29.2mm)	BK	<input type="checkbox"/> L1530PWBK	<input type="checkbox"/> L1530CWBK		
			3Ø severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	<input type="checkbox"/> L1530PY	<input type="checkbox"/> L1530CY		
			3Ø safety grip corrosion resistant	0.63-1.16" (15.9-29.4mm)	Y	<input type="checkbox"/> CRL1530P	<input type="checkbox"/> CRL1530C		

3Ø receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.		
30	250	L15-30	3Ø watertight	Y	<input type="checkbox"/> L1530RW		
			3Ø watertight	BK	<input type="checkbox"/> L1530RWBK		

Color information:

BK (Black), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32

Locking devices

Complex environment locking devices

Product description

3-pole, 4-wire grounding
30A, 125/250V/AC
NEMA L14-30




L14-30R L14-30P




CRL1430P



CRL1430C



CRL1430R



L1430RW

Dimensional information:
D-34-35

Specification information:
Watertight industrial plugs & connectors: D-38
Watertight industrial receptacles: D-39
Severe duty industrial plugs & connectors: D-40
Corrosion resistant: D-41

Plugs & connectors

Rating	A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.	
30	125/250	L14-30	Watertight	0.43-1.15" (10.9-29.2mm)	Y	□ L1430PW	□ L1430CW	• •	
			Watertight	0.43-1.15" (10.9-29.2mm)	BK	□ L1430PWBK	□ L1430CWBK	• •	
			Severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	□ L1430PY	□ L1430CY	• •	
			Safety grip corrosion resistant	0.63-1.16" (15.9-29.4mm)	Y	□ CRL1430P	□ CRL1430C	• •	

Receptacles


Rating	A	V/AC	NEMA	Description	Color	Single receptacle catalog no.	
30	125/250	L14-30	Watertight	Y	□ L1430RW	• •	
			Watertight	BK	□ L1430RWBK	• •	
			Corrosion resistant	Y	□ CRL1430R*	• •	

* Only UL Listed, CSA certified and Fed Spec certified

Complex environment locking devices

Product description

3-pole, 4-wire grounding
30A, 3Ø 250V/AC
NEMA L15-30



L15-30R L15-30P

3Ø plugs & connectors

Rating	A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.	
30	250	L15-30	3Ø watertight	0.43-1.15" (10.9-29.2mm)	Y	□ L1530PW	□ L1530CW	• •	
			3Ø watertight	0.43-1.15" (10.9-29.2mm)	BK	□ L1530PWBK	□ L1530CWBK	• •	
			3Ø severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	□ L1530PY	□ L1530CY	• •	
			3Ø safety grip corrosion resistant	0.63-1.16" (15.9-29.4mm)	Y	□ CRL1530P	□ CRL1530C	• •	

3Ø receptacles

Rating	A	V/AC	NEMA	Description	Color	Single receptacle catalog no.	
30	250	L15-30	3Ø watertight	Y	□ L1530RW	• •	
			3Ø watertight	BK	□ L1530RWBK	• •	

Color information:

BK (Black), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32