



Turnlok® Single Receptacle, 3-Wire 30A 480V

## Features & Benefits

Compact, impact-resistant nylon face and body are ultrasonically welded together for unrivaled strength.

One piece, high-grade brass contacts offer excellent conductivity and heat-rise resistance.

Single-piece, solid brass mounting strap is free of easily loosened rivets found on other brands.

Accepts #14 - #10 AWG.

Face color coding by voltage facilitates locating and mating of proper devices.

Clearly marked NEMA configuration, rating, and third-party listing on each unit's face.

Side and external screw-pressure-plate back wire capability.

## Specifications

### General Info

|                       |                         |                    |                                        |
|-----------------------|-------------------------|--------------------|----------------------------------------|
| Product Line          | Pass & Seymour          | Color              | Black                                  |
| UPC Number            | 785007283051            | Country Of Origin  | Mexico                                 |
| Number of Receptacles | 1                       | Features           | Brass Mounting Strap, Impact Resistant |
| Outlet Type           | Locking                 | Application Sector | Commercial                             |
| Wall Plate Included   | No                      | Standard           | UL 498                                 |
| Warranty Type         | 1-Year Limited Warranty |                    |                                        |

### Dimensions

|                  |         |
|------------------|---------|
| Product Width US | 1.61 in |
|------------------|---------|

Listing Agencies / 3rd Party Agencies

|                     |        |              |     |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | 140596 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

Additional Information

|                               |     |
|-------------------------------|-----|
| Product Environmental Profile | Yes |
|-------------------------------|-----|

Technical Information

|                     |               |       |       |
|---------------------|---------------|-------|-------|
| Connection Location | Back and Side | Phase | Three |
|---------------------|---------------|-------|-------|

|                 |   |          |      |
|-----------------|---|----------|------|
| Number of Wires | 3 | Amperage | 30 A |
|-----------------|---|----------|------|

|                 |             |           |             |
|-----------------|-------------|-----------|-------------|
| Number of Poles | Double Pole | Wire Size | 14 - 10 AWG |
|-----------------|-------------|-----------|-------------|

|                |        |                         |        |
|----------------|--------|-------------------------|--------|
| Indoor/Outdoor | Indoor | NEMA Configuration Code | L8-30R |
|----------------|--------|-------------------------|--------|

|                      |                 |         |         |
|----------------------|-----------------|---------|---------|
| Wire Connection Type | Screw Terminals | Voltage | 480.0 V |
|----------------------|-----------------|---------|---------|



Turnlok® Single Receptacle, 3-Wire 30A 480V

## Features & Benefits

Compact, impact-resistant nylon face and body are ultrasonically welded together for unrivaled strength.

One piece, high-grade brass contacts offer excellent conductivity and heat-rise resistance.

Single-piece, solid brass mounting strap is free of easily loosened rivets found on other brands.

Accepts #14 - #10 AWG.

Face color coding by voltage facilitates locating and mating of proper devices.

Clearly marked NEMA configuration, rating, and third-party listing on each unit's face.

Side and external screw-pressure-plate back wire capability.

## Specifications

### General Info

|                       |                         |                    |                                        |
|-----------------------|-------------------------|--------------------|----------------------------------------|
| Product Line          | Pass & Seymour          | Color              | Black                                  |
| UPC Number            | 785007283051            | Country Of Origin  | Mexico                                 |
| Number of Receptacles | 1                       | Features           | Brass Mounting Strap, Impact Resistant |
| Outlet Type           | Locking                 | Application Sector | Commercial                             |
| Wall Plate Included   | No                      | Standard           | UL 498                                 |
| Warranty Type         | 1-Year Limited Warranty |                    |                                        |

### Dimensions

|                  |         |
|------------------|---------|
| Product Width US | 1.61 in |
|------------------|---------|

Listing Agencies / 3rd Party Agencies

|                     |        |              |     |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | 140596 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

Additional Information

|                               |     |
|-------------------------------|-----|
| Product Environmental Profile | Yes |
|-------------------------------|-----|

Technical Information

|                     |               |       |       |
|---------------------|---------------|-------|-------|
| Connection Location | Back and Side | Phase | Three |
|---------------------|---------------|-------|-------|

|                 |   |          |      |
|-----------------|---|----------|------|
| Number of Wires | 3 | Amperage | 30 A |
|-----------------|---|----------|------|

|                 |             |           |             |
|-----------------|-------------|-----------|-------------|
| Number of Poles | Double Pole | Wire Size | 14 - 10 AWG |
|-----------------|-------------|-----------|-------------|

|                |        |                         |        |
|----------------|--------|-------------------------|--------|
| Indoor/Outdoor | Indoor | NEMA Configuration Code | L8-30R |
|----------------|--------|-------------------------|--------|

|                      |                 |         |         |
|----------------------|-----------------|---------|---------|
| Wire Connection Type | Screw Terminals | Voltage | 480.0 V |
|----------------------|-----------------|---------|---------|