


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





LPJ150SPI Indicating LPJ-150SP *Bussmann Fuses*

Catalog Number	LPJ150SPI
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class J Fuse, LPJ, Time-Delay,
	Dual-Element Current Limiting Fuse, 150 A, Indicating Fuse,
	Interrupting Rating Of 300 Ka At 600 Vac
Weight per unit	0.7800 (lbs/each)
Product Category	Small Dimension Fuses

Features

amperage rating	150 A
class	Class J
connection	Bolted Blade End X Bolted Blade End
dimensions	2.2500 IN X 0.8100 IN X 0.8100 IN
element	Dual
Fuse Class	Class J
interrupt rating	300 kAIC at 600 Vac100 kAIC Vdc
media	Yes
Response Time	10 sec at 500%
Voltage Rating	600 Vac, 300 Vdc

Dimensions and Weight

Size 1.63 In Diameter X 5.75 In Length

Descriptions

Description	INDICATING LPJ-150SP
extra long description	BUSS LPJ-150SPI LOW-PEAK CLASS J IN
Features	Bussmann's UL Class J fuse products extend both our Low-Peak family of products with our LPJ_SP and LPJ_SPI dual-element, time-delay fuses as well as our Limitron line offering fast-acting JKS fuses. The LPJ fuses provide industry leading 300,000 amp interrupting rating at 600Vac RMS Sym and 100kA Vdc while delivering a minimum of 10 seconds of 500 percent rated current ride-through performance which is ideal for sizing of high inrush loads. The LPJ products are available with optional permanent replace fu
Long Description	Eaton Bussmann Series Class J fuse, LPJ, time-delay, dual-element current limiting fuse, 150 A, indicating fuse, interrupting rating of 300 kA at 600 Vac
Product Type	Low-Peak Class J Indicating T/D
Special Features	Indicating, High in-rush current motor protection



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	Inform	

Brand	Eaton Bussmann series
GTIN	00051712627993
Manufacturers Part Number	LPJ-150SPI
UPC	051712627993

Taxonomies, Classifications, and Categories

Category Description	GLASS FUSES (and ceramic)
Type	FUSE

Packaging

···-g···g	
Carton	1
Weight Per each	0.78

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked,RoHS Compliant