

## ELLIOTT ELECTRIC SUPPLY Ma Deliver Lower Cost. Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## LT400G 4" LT Conn Ground 3/0 Crouse-Hinds

E	
Catalog Number	LT400G
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FM Straight, Aluminum Ground Lug, Non-Insulated, #3/0-6 Awg Lug Size, Malleable Iron, 4"
Weight per unit	8.1 (lbs/each)
Product Category	Liquid Tight Fittings
eatures	
connection	Threaded
dimensions	4.0000 IN X 5.7500 IN X 5.7500 IN
installation type	THREADED
laterial, Color, and Finish	
Color	MALLEABLE IRON
escriptions	
Description	4" LT CONN GROUND 3/0
extra long description	MIDWEST LT400G 4 LT CONN GRND 3/0
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC Straight, Aluminum ground lug, Non-insulated, #3/0-6 AWG lug size, Malleable iron, 4"
Product Type	4 LT Conn GRND 3/0
Special Features	With 6 To 3/0 AWG Aluminum Grounding Lug
lanufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564260109
Manufacturers Part Number	LT400G
UPC	784564260109
axonomies, Classifications, and (	Categories
Category Description	
Туре	Liquidtight connector



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

Trade Size Trade Size	4 in
Packaging	1
Weight Per each	8.05
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.2