



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## **LTB30045 3" 45D LT Conn** *Crouse-Hinds*

Catalog Number	LTB30045
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 45° Angle, Insulated, Malleable Iron, 3"
Weight per unit	8.7 (lbs/each)
Product Category	Liquid Tight Fittings

### **Features**

connection	Threaded
dimensions	8.7500 IN X 4.1900 IN X 8.7500 IN
installation type	THREADED

### **Material, Color, and Finish**

Color	MALLEABLE IRON
-------	----------------

### **Descriptions**

Description	3" 45D LT CONN
extra long description	MIDWEST LTB30045 3 LT 45 DEGREE CON
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Insulated, Malleable iron, 3"
Product Type	3 LT 45 Degree Conn Insulated

### **Manufacturer Information**

Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564463005
Manufacturers Part Number	LTB30045
UPC	784564463005

### **Taxonomies, Classifications, and Categories**

Category Description	METALLIC FITTINGS
Type	Liquidtight connector

### **Trade Size**

Trade Size	3 in
------------	------



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	1
Weight Per each	8.65

## Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.109