



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

6312A Airport Freeway
76117-0000, TX Ft. Worth
Phone: 682-647-1594
Fax: 682-647-1528



LTB5045 1/2" 45D LT Conn Ins

Crouse-Hinds

Catalog Number	LTB5045
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 45° Angle, Insulated, Malleable Iron, 1/2"
Weight per unit	0.3000 (lbs/each)
Product Category	Liquid Tight Fittings

Features

connection	Threaded
dimensions	2.5000 IN X 1.2500 IN X 2.5000 IN
installation type	THREADED

Material, Color, and Finish

Color	MALLEABLE IRON
-------	----------------

Descriptions

Description	1/2" 45D LT CONN INS
extra long description	MIDWEST LTB5045 1/2 LT 45 DEGREE CO
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Insulated, Malleable iron, 1/2"
Product Type	1/2 LT 45 Degree Conn Insulated

Manufacturer Information

Brand	Eaton
GTIN	00784564460509
Manufacturers Part Number	LTB5045
UPC	784564460509

Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Type	Liquidtight connector

Trade Size

Trade Size	1/2 in
------------	--------



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

6312A Airport Freeway
76117-0000, TX Ft. Worth
Phone: 682-647-1594
Fax: 682-647-1528

Packaging

Carton	25
Weight Per each	0.3

Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.81