



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## MAASIV Maestro Accessory Switch Ivory

Lutron

Catalog Number	MAASIV
Manufacturer	Lutron
Description	Maestro Companion Switch For Multi-Location Use, 120V, Gloss Finish In Ivory
Weight per unit	0.3500 (lbs/each)
Product Category	Lighting Controls

### Features

Material	Plastic/Metal
Poles	1

### Material, Color, and Finish

Color	Ivory
Finish	Gloss

### Descriptions

Description	MAESTRO ACCESSORY SWITCH IVORY
extra long description	LUT MA-AS-IV MAESTRO ACCESSORY SWIT
Features	The Maestro companion switch is designed to complement a Maestro switch. The easy-to-operate tap switch turns lights on and off. Up to 9 companion switches can be linked to a Maestro switch, for a total of 10 areas of control. Maestro accessories provide light control convenience for hallways, stairways or any room with multiple switch controls. Coordinating Claro wall plate sold separately.
Long Description	Maestro Companion switch for multi-location use, 120V, Gloss finish in ivory
Product Type	Maestro Accessory Switch Ivory
Special Features	For use with multi-location switches; use up to 9 companion switches with only one Maestro multi-location switch. Can be used with multi-location countdown timer switch. Use standard 3-way wiring. 120V

### Manufacturer Information

Brand	Lutron
GTIN	00027557082693
Manufacturers Part Number	MA-AS-IV
UPC	027557082693

### Taxonomies, Classifications, and Categories

Category Description	Residential dimmers, motion sensors, controls, & photo cells
Type	Companion switch



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	24
Package	48
Weight Per each	0.35

## Uses, Certifications, and Standards

Application	Lighting Control
Enclosure	Plastic
Mounting	WALLBOX
Operating Temperature	32 to 104
standard	UL, cUL, CSA, FCC, IC